117-201 Q&As

Linux Advanced Administration

Pass Lpi 117-201 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.passapply.com/117-201.html

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Lpi Official Exam Center

- **Instant Download** After Purchase
- **100% Money Back** Guarantee
- **365 Days** Free Update
- **800,000+** Satisfied Customers

QUESTION 1

Which site-specific configuration file for the shadow login suite must be modified to log login failures?

Please enter the complete path to that file.

Correct Answer: fetcflog.defs

QUESTION 2

Messages from programs are not appearing in the user\\'s native language. What environment variable must be set for this to happen?

A. LANG

B. Il8N

C. MESSAGES

D. MSGS

E. LC_MSGS

Correct Answer: A

QUESTION 3

Which of the following commands should be used in a bash script that needs a variable containing the IP address of the eth0 interface? The output for the command ifconfig eth0 is shown below: eth0 Link encap:Ethernet HWaddr 00:0C:29:CB:FA:30 inetaddr:192.168.246.llBcast:192.168.246.255Mask:255.255.255.0UPBROADCAST UNNING MULTICAST MTU:1500 Metric:l RX packets:4721 errors:0 dropped:0 overruns:0 frame:0 TX packets:3216 errors:0 dropped:0 overruns:0 carrier:0 collisions:0 txqueuelen:1000 RX bytes:445184 (434.7 Kb) TX bytes:512968 (500.9 Kb) Interrupt:l85 Base address:0x1080

A. IP=LANG= ifconfig eth0 I awk \\'{ print $2 }\\' I cut -f2

B. IP=LANG= ifconfig eth0 I grep inet I cut -d: -f2 I awk { print $l }

C. IP=LANG= ifconfig eth0 I awk \\'{ print $3 }\\'

D. IP=$(LANG= ifconfig eth0 I grep inet I awk \\'{ print $2 }\\' I cut -d: -f2)

E. IP=$(LANG= ifconfig eth0 I grep inet I cut -d: -f2)

Correct Answer: D

QUESTION 4

An administrator has placed an executable in the directory /etc/init.d, however it is not being executed when the system

boots into runlevel 2. What is the most likely cause of this?

A. The script has not been declared in /etc/services

B. runlevel 2 is not declared in /etc/inittab

C. The script has the permissions 700 and is owned by root

D. A corresponding link was not created in /etc/rc2.d

Correct Answer: D

QUESTION 5

After calling ./configure with its appropriate parameters and no errors, what would be the next command to

run?

Correct Answer: make all -ormake

Latest 117-201 Dumps 117-201 Study Guide 117-201 Exam Questions