



# 156-215.77<sup>Q&As</sup>

Check Point Certified Security Administrator

## Pass CheckPoint 156-215.77 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/156-215-77.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by CheckPoint Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





#### QUESTION 1

Which of the following authentication methods can be configured in the Identity Awareness setup wizard?

- A. Check Point Password
- B. TACACS
- C. LDAP
- D. Windows password

Correct Answer: C

---

#### QUESTION 2

Which of the following authentication methods can be configured in the Identity Awareness setup wizard?

- A. TACACS
- B. Captive Portal
- C. Check Point Password
- D. Windows password

Correct Answer: B

---

#### QUESTION 3

You are the Security Administrator for MegaCorp. A Check Point firewall is installed and in use on a platform using GAiA. You have trouble configuring the speed and duplex settings of your Ethernet interfaces. Which of the following commands can be used in CLISH to configure the speed and duplex settings of an Ethernet interface and will survive a reboot? Give the BEST answer.

- A. ethtool
- B. set interface
- C. mii\_tool
- D. ifconfig -a

Correct Answer: B

---

#### QUESTION 4

A Web server behind the Security Gateway is set to Automatic Static NAT. Client side NAT is not checked in the Global Properties. A client on the Internet initiates a session to the Web Server. Assuming there is a rule allowing this traffic,



what other configuration must be done to allow the traffic to reach the Web server?

- A. Automatic ARP must be unchecked in the Global Properties.
- B. Nothing else must be configured.
- C. A static route must be added on the Security Gateway to the internal host.
- D. A static route for the NAT IP must be added to the Gateway's upstream router.

Correct Answer: C

---

#### QUESTION 5

After filtering a fw monitor trace by port and IP, a packet is displayed three times; in the i, I, and o inspection points, but not in the O inspection point. Which is the likely source of the issue?

- A. The packet has been sent out through a VPN tunnel unencrypted.
- B. An IPSO ACL has blocked the packet's outbound passage.
- C. A SmartDefense module has blocked the packet.
- D. It is due to NAT.

Correct Answer: D

[156-215.77 PDF Dumps](#)

[156-215.77 VCE Dumps](#)

[156-215.77 Exam Questions](#)