



1D0-437^{Q&As}

CIW PERL FUNDAMENTALS

Pass CIW 1D0-437 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/1d0-437.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by CIW Official Exam Center

- ⚙ **Instant Download** After Purchase
- ⚙ **100% Money Back** Guarantee
- ⚙ **365 Days** Free Update
- ⚙ **800,000+** Satisfied Customers





QUESTION 1

Consider the following program code: `%_Nifty = (one, two, three, four); @NiftyKeys = sort(keys(%_Nifty));`

```
foreach (@NiftyKeys)
{
    print ($_Nifty{$_} . );
}
```

What is the result of executing this program code?

- A. The code will output the following: one three
- B. The code will output the following: four two
- C. The code will output the following: two four
- D. The code will output the following: four one three two

Correct Answer: C

QUESTION 2

Which statement will print the capital attribute of the `$kansas` object?

- A. `print ("capital"=>$kansas);`
- B. `print {$kansas}>=>(capital);`
- C. `print (capital){"capital"};`

Correct Answer: D

QUESTION 3

Consider the following program code:

```
@arrayA = (10, 20, 30);
$arrayB = @arrayA;
$arrayB[1] = 40;
print $arrayA[1];
```

What is the output of this code?

- A. 10



B. 20

C. 30

D. 40

Correct Answer: B

QUESTION 4

Consider the following program code:

```
$x = 150;
```

```
$y = "250";
```

```
if (($x + 100) == $y) { print("1 "); }
```

```
if ("250" == $y) { print("2 "); }
```

```
if ("250" eq $y) { print("3 "); }
```

```
if ($x lt $y) { print("4 "); }
```

```
if ($x ge $y) { print("5 "); }
```

What is the result of executing this program code?

A. The code will output the following: 1 2 3 4

B. The code will output the following: 1 3 4

C. The code will output the following: 1 3 5

D. The code will output the following: 1 2 3 4 5

Correct Answer: A

QUESTION 5

Which of the following choices demonstrates the correct syntax for creating a hash?

A. `%passwd = ("denise", "robert", "yolanda") => ("pass1", "pass2", "pass3");`

B. `%passwd() = ("denise", "pass1", "robert", "pass2", "yolanda", "pass3");`

C. `%passwd = (denise=> "pass1", robert=> "pass2", yolanda=> "pass3");`

D. `%passwd{3} = ("denise", "robert", "yolanda") => ("pass1", "pass2", "pass3");`

Correct Answer: C



VCE & PDF

PassApply.com

<https://www.passapply.com/1d0-437.html>

2024 Latest passapply 1D0-437 PDF and VCE dumps Download

[1D0-437 Practice Test](#)

[1D0-437 Exam Questions](#)

[1D0-437 Braindumps](#)