



# 1Y0-A21<sup>Q&As</sup>

Basic Administration for Citrix NetScaler 9.2

## Pass Citrix 1Y0-A21 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/1y0-a21.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Citrix  
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





### QUESTION 1

Which IP address type must be unique to each NetScaler in an HA pair?

- A. MIP
- B. NSIP
- C. SNIP
- D. Load balancing VIP

Correct Answer: B

---

### QUESTION 2

Scenario: An administrator has set up a NetScaler in HA mode and now wants to bind the SSL certificate to one of the SSL virtual servers. However, the administrator notices that the command failed on the secondary node while succeeding on the primary node. Both nodes in HA are healthy, with successful configuration synchronization and command propagation.

Which reason explains the command failure on the secondary node?

- A. Command syntax is not correct.
- B. Command not executed with root ID.
- C. SSL command not available on secondary node.
- D. SSL certificate is not present on secondary node.

Correct Answer: D

---

### QUESTION 3

Scenario: An administrator needs to configure SSL offloading on a NetScaler system. The administrator has already enabled SSL on the NetScaler, added the necessary service and added an SSL-based virtual server.

Which three additional steps must the administrator take to complete the SSL offloading configuration? (Choose three.)

- A. Create load balancing virtual servers.
- B. Bind the created service to the virtual server.
- C. Add a wildcard certificate to the virtual server.
- D. Add an SSL certificate key pair to the NetScaler.
- E. Bind the SSL certificate key pair to the virtual server.
- F. Obtain an SSL certificate from an authorized certificate authority (CA).



Correct Answer: BDE

---

#### QUESTION 4

An administrator needs to configure a NetScaler system in a manner that will increase the capacity and availability of a single communication channel between the NetScaler and another connected device. What should the administrator configure on the NetScaler system to achieve this requirement?

- A. NIC teaming
- B. Link Bonding
- C. Link Aggregation
- D. Interface Trunk mode

Correct Answer: C

---

#### QUESTION 5

Which page is displayed to the user if a catch-all policy is NOT defined on a content switching virtual server configured on the NetScaler?

- A. Users get an HTTP/1.1 Error.
- B. Users get an Access Denied Page.
- C. The policy with the lowest priority gets evaluated.
- D. Users are redirected to the page configured in the redirectURL parameter of the CSV server.

Correct Answer: A

[1Y0-A21 VCE Dumps](#)

[1Y0-A21 Study Guide](#)

[1Y0-A21 Exam Questions](#)