



# 1Z0-062<sup>Q&As</sup>

Oracle Database 12c: Installation and Administration

## Pass Oracle 1Z0-062 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/1z0-062.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Oracle  
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





### QUESTION 1

The HR.DEPARTMENTS table is the parent of the HR.EMPLOYEES table. The EMPLOYEES.DEPARTMENT\_ID column has a foreign key constraint with the ON DELETE CASCADE option that refers to the DEPARTMENTS.DEPARTMENT\_ID column. An index exists on the DEPARTMENTS.DEPARTMENT\_ID column. A transaction deletes a primary key in the DEPARTMENTS table, which has child rows in the EMPLOYEES table.

Which statement is true?

- A. The transaction acquires a table lock only on the DEPARTMENTS table until the transaction is complete.
- B. The transaction acquires a table lock on the DEPARTMENTS table. This lock enables other sessions to query but not update the DEPARTMENTS table until the transaction on the DEPARTMENTS table is complete.
- C. The transaction acquires a table lock on the EMPLOYEES table. This lock enables other sessions to query but not update the EMPLOYEES table until the transaction on the DEPARTMENTS table is complete.
- D. Only the rows that are deleted in the DEPARTMENTS and EMPLOYEES tables are locked until the transactions on the DEPARTMENTS table is complete.

Correct Answer: C

---

### QUESTION 2

Which three are true about the default database buffer cache? (Choose three.)

- A. Buffers containing block images may be selected for reuse based only on a Least Recently Used (LRU) algorithm.
- B. It is in the fixed area of the SGA.
- C. Its buffers can contain data block images for blocks that have a corresponding image in a data file.
- D. Buffers containing block images may be selected for reuse based only on a touch count algorithm.
- E. It can contain block images only for database blocks whose block size is equal to the buffer size.
- F. The keep and recycle cache memory is sub-allocated from memory allocated to the default buffer cache.
- G. Its buffers can contain data block images for blocks that have no corresponding image in a data file.

Correct Answer: BFG

---

### QUESTION 3

Examine the following parameters for a database instance:

MEMORY\_MAX\_TARGET=0 MEMORY\_TARGET=0 SGA\_TARGET=0 PGA\_AGGREGATE\_TARGET=500m

Which three initialization parameters are not controlled by Automatic Shared Memory Management (ASMM)? (Choose three.)



- A. LOG\_BUFFER
- B. SORT\_AREA\_SIZE
- C. JAVA\_POOL\_SIZE
- D. STREAMS\_POOL\_SIZE
- E. DB\_16K\_CACHE\_SIZE
- F. DB\_KEEP\_CACHE\_SIZE

Correct Answer: AEF

Manually Sized SGA Components that Use SGA\_TARGET Space SGA Component, Initialization Parameter / The log buffer LOG\_BUFFER / The keep and recycle buffer caches DB\_KEEP\_CACHE\_SIZE DB\_RECYCLE\_CACHE\_SIZE / Nonstandard block size buffer caches DB\_nK\_CACHE\_SIZE

Note:

\*

In addition to setting SGA\_TARGET to a nonzero value, you must set to zero all initialization parameters listed in the table below to enable full automatic tuning of the automatically sized SGA components.

\*

Table, Automatically Sized SGA Components and Corresponding Parameters

SGA Component	Initialization Parameter
Fixed SGA and other internal allocations needed by the Oracle Database instance	N/A
The shared pool	SHARED_POOL_SIZE
The large pool	LARGE_POOL_SIZE
The Java pool	JAVA_POOL_SIZE
The buffer cache	DB_CACHE_SIZE
The Streams pool	STREAMS_POOL_SIZE

#### QUESTION 4

In which situations does the Database Writer process (DBWn) write to data files? (choose two).

- A. when the RMAN recovery process starts
- B. when a user process commits a transaction
- C. when a tablespace is made read-only or taken offline
- D. when PMON cleans up dirty buffers in the database buffer cache
- E. when clean buffers for reading new blocks into the database buffer cache are not found easily

Correct Answer: BD



References: [https://docs.oracle.com/cd/B19306\\_01/server.102/b14220/process.htm](https://docs.oracle.com/cd/B19306_01/server.102/b14220/process.htm)

---

### QUESTION 5

Which statement is true regarding the DEFAULT profile?

- A. The values assigned to the resource limits and password parameters in the default profile can be altered.
- B. A different DEFAULT profile can be created before each user in a database.
- C. It can be dropped and recreated.
- D. it must be explicitly assigned to the user.

Correct Answer: A

[1Z0-062 PDF Dumps](#)

[1Z0-062 Practice Test](#)

[1Z0-062 Exam Questions](#)