



1Z0-822^{Q&As}

Oracle Solaris 11 Advanced System Administration

Pass Oracle 1Z0-822 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/1z0-822.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Oracle
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

Review the following output from the zpool status command:

```
pool: pool1
state: ONLINE
scan: none requested
config:

    NAME            STATE        READ  WRITE CKSUM
    pool1           ONLINE      0     0     0
      mirror-0      ONLINE      0     0     0
        c3t3d0      ONLINE      0     0     0
        c3t4d0      ONLINE      0     0     0
      mirror-1      ONLINE      0     0     0
        c3t5d0      ONLINE      0     0     0
        c3t6d0      ONLINE      0     0     0

errors: No known data errors
```

Which three are true for pool1?

- A. If this mirror is split, the new pool will contain disks c3t5d0 and c3t6d0.
- B. If this mirror is split, by default the new pool will contain disks c3t3d0 and c3t5d0.
- C. Data is striped across mirror-0 and mirror-1.
- D. mirror-1 is a mirrored copy of data that is stored on mirror-0.
- E. Disk c3t3d0 is a mirrored copy of disk c3c4d0.
- F. If this mirror is split, pool1 will no longer be mirrored.

Correct Answer: BDE

QUESTION 2

What is true about crash dump configuration?

- A. The minfree value can be to protect a percentage of available disk space.
- B. The default size of the dump device is configurable.
- C. You can use one ZFS volume for both swap and dump.
- D. You can set quota on a ZFS dump device.
- E. When set on the dump device, the minfree value sets the total size of the dump device to be a percentage of the total size of the root pool.

Correct Answer: C



QUESTION 3

Your organization uses NFS to share data from Oracle Solaris servers to Oracle Solaris clients. The server currently has an NFS share configured for the `rpool/export/data` file system. A client is currently mounting this file system. As administrator, you add a new file system `rpool/export/data/yesterdays_data`, and copy data into the new file system. Which action is required for the client currently mounting the `rpool/expor/data` file system to access the new data?

- A. The `rpool/export/data/yesterdays_data` file system must be mounted.
- B. No action is required because the data is automatically made available.
- C. The `rpool/export/data` file system must be remounted.
- D. The `nfs/client` server must be restarted.

Correct Answer: C

QUESTION 4

Which two statements are correct regarding IPS repositories?

- A. Remote client access is governed by `svc:/application/pkg/server`.
- B. Every new repository contains the solaris publisher by default.
- C. One repository can replicate the contents of another.
- D. The `pkg.depotd` process makes all local repositories remotely available.
- E. A repository uses separate protocols for `pkg` and browser clients.

Correct Answer: CE

QUESTION 5

What are targets for IPMP probe-based failure detection configured by?

- A. responses to SNMP requests
- B. specifying host routes in the routing table
- C. specifying hosts in `/etc/default/mpathd`
- D. setting the property `svc:/network/ipmp/config/transitive-probing`

Correct Answer: B