

# 1Y0-241<sup>Q&As</sup>

Deploy and Manage Citrix ADC with Traffic Management

# Pass Citrix 1Y0-241 Exam with 100% Guarantee

Free Download Real Questions & Answers PDF and VCE file from:

https://www.passapply.com/1y0-241.html

100% Passing Guarantee 100% Money Back Assurance

Following Questions and Answers are all new published by Citrix
Official Exam Center

- Instant Download After Purchase
- 100% Money Back Guarantee
- 365 Days Free Update
- 800,000+ Satisfied Customers



# VCE & PDF PassApply.com

### https://www.passapply.com/1y0-241.html

2024 Latest passapply 1Y0-241 PDF and VCE dumps Download

#### **QUESTION 1**

A Citrix Administrator needs to configure a rate-limiting policy setting DNS requests to a threshold of 1,000 per second. Which command does the administrator need to run to correctly configure this policy?

- A. HTTP.REQ.LIMIT()
- B. SYS.CHECK.LIMIT()
- C. SYS.CHECK.LIMIT() || CONNECTION.IP.LIMIT()
- D. SYS.CHECK.LIMIT() || HTTP.REQ.LIMIT()

Correct Answer: B

https://docs.citrix.com/en-us/citrix-adc/current-release/appexpert/rate-limiting/configuring-binding-traffic-rate-policy1.html https://discussions.citrix.com/topic/398863-netscaler-rate-limiting-policy/

#### **QUESTION 2**

Scenario: To receive data alerts for failures, a Citrix Administrator is configuring SNMP on the Citrix ADC. The administrator is confident that the manager, alarms and SNMP traps are configured correctly. The following week, there is a Citrix ADC-related outage and the administrator does NOT receive any alerts.

What could be the reason for this alert failure?

- A. The Citrix Web App Firewall is blocking the alerts from going out.
- B. The community name was NOT configured in the Citrix ADC SNMP trap destination settings.
- C. The Citrix ADC only has standard licensing.
- D. The Citrix ADC is configured for SNMP version 1.

Correct Answer: B

#### **QUESTION 3**

Scenario: The primary content switching vServer has gone down. To troubleshoot, a Citrix Administrator has issued the following command: > show csvserver CSV CSV (10.1.100.100:443) ?HTTPS Type: CONTENT State: UP Last state change was at Mon Jun 29 15:20:43 2020 Time since last state change: 1 day, 06:47:58 610 Client Idle Timeout: 180 sec Down state flush: ENABLED Disable Primary vServer On Down: DISABLED Appflow logging: ENABLED Port Rewrite: DISABLED State Update: DISABLED Default: Content Precedence: URL vServer IP and Port insertion: OFF Persistence: NONE redirect: http://www.site1.com/mysite1/maintenance Backup: vServer-LB-2 Listen Policy: NONE IcmpResponse: PASSIVE RHIstate: PASSIVE Traffic Domain: 0 Based on this output, where will the subsequent request be redirected?

- A. http://www.site1.com/mysite1/maintenance
- B. vServer-LB-2



## https://www.passapply.com/1y0-241.html

2024 Latest passapply 1Y0-241 PDF and VCE dumps Download

C. Backup content switching vServer

D. 10.1.100.100:443

Correct Answer: B

https://docs.citrix.com/en-us/citrix-adc/current-release/content-switching/protecting-against- failure.html#configuring-a-redirection-url "If a content switching virtual server is configured with both a backup virtual server and a redirect URL, the backup virtual server takes precedence over the redirect URL. A redirect URL is used when the primary and backup virtual servers are down."

#### **QUESTION 4**

A Citrix Administrator configured global server load balancing (GSLB) for www.citrix.com, with two ADNS services named Citrix ADC 1 and Citrix ADC 2 in the setup. Which record does the administrator need to add on the parent DNS server to delegate requests from www.citrix.com to Citrix ADC 1 and Citrix ADC 2?

- A. Canonical Name (CNAME)
- B. Address (A) record
- C. Name Server (NS) record
- D. Pointer Record (PTR)

Correct Answer: C

https://docs.citrix.com/en-us/citrix-adc/current-release/global-server-load-balancing/how-dns-works-with-gslb.html

#### **QUESTION 5**

A Citrix Administrator needs to use a client\\'s IP address as the source IP address for Citrix ADC-to-server connections. Which Citrix ADC mode can the administrator use to meet this requirement?

- A. USNIP
- B. Layer 2
- C. Layer 3
- D. USIP

Correct Answer: D

When you enable the USIP address mode of a NetScaler appliance, the appliance forwards each packet to the appropriate back end server with the client IP address. https://support.citrix.com/article/CTX121974

1Y0-241 VCE Dumps

1Y0-241 Exam Questions

1Y0-241 Braindumps