



1Y0-253^{Q&As}

Implementing Citrix NetScaler 10.5 for App and Desktop Solutions

Pass Citrix 1Y0-253 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/1y0-253.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Citrix
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

Which two steps must a Citrix Administrator take to allow additional users to access resources using the NetScaler Gateway Plug-in after the administrator installs the universal license on the NetScaler Gateway? (Choose two.)

- A. Set ICA Proxy to OFF.
- B. Configure Citrix Receiver Home Page.
- C. Change the authentication AAA settings.
- D. Set Single Sign-on with Windows to OFF.

Correct Answer: AC

QUESTION 2

Scenario: A Citrix Administrator would like to delegate administration of the Citrix NetScaler to a Microsoft Active Directory group called ICitrix-NetScaler-Admins. The group already exists in Active Directory. The Citrix-NetScaler-Admins group must have full-control permission on the Citrix NetScaler to perform their tasks. The administrator has successfully configured an LDAP authentication server and authentication policy. The authentication policy is already globally bound. How should the administrator proceed on the Citrix NetScaler?

- A. Create an AAA User called Citrix-NetScaler-Admins and select IExternal Authentication.
- B. Create a group called Citrix-NetScaler-Admins. Make the group a member of the operator command policy.
- C. Create a group called Citrix-NetScaler-Admins. Make the group a member of the superuser command policy.
- D. Create an AAA group called Citrix-NetScaler-Admins. Create an ALLOW authorization policy and bind it to the Citrix-NetScaler-Admins AAA Group.

Correct Answer: C

QUESTION 3

Scenario: A NetScaler Gateway is configured to use RADIUS for authentication. A Citrix Administrator needs to know which NetScaler IP (NSIP) address is used for outgoing RADIUS traffic.

How can the administrator verify which NSIP is used?

- A. Check the ns.log file.
- B. Use the ping command.
- C. Check the messages log file.
- D. Use the nstcpdump.sh command.

Correct Answer: D



QUESTION 4

A Citrix Administrator is replacing an expired SSL certificate bound to a virtual server. The established ICA connections to the virtual server will display as . (Choose the correct option to complete the sentence.)

- A. logged off
- B. terminated
- C. disconnected
- D. uninterrupted

Correct Answer: C

QUESTION 5

Scenario: A Citrix Administrator has implemented a remote access solution using NetScaler. The administrator is alerted with information indicating users attempting to access resources through NetScaler are unable to authenticate.

How can the administrator identify whether the authentication process is the cause?

- A. Review the system log on the Domain Controller.
- B. Execute the `Insconmsg -d eventl` command on the NetScaler.
- C. Use the `lcat aaad.debugl` command on the NetScaler shell.
- D. Use the `lvi jvarjlogjauth error.logl` command to review saved events on the NetScaler shell.

Correct Answer: C

[Latest 1Y0-253 Dumps](#)

[1Y0-253 PDF Dumps](#)

[1Y0-253 VCE Dumps](#)