



1Y0-351^{Q&As}

Citrix NetScaler 10.5 Essentials and Networking

Pass Citrix 1Y0-351 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/1y0-351.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Citrix
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

Server Name Indication (SNI) is required when _____. (Choose the correct option to complete the sentence.)

- A. TLS 1.1/1.2 is enabled exclusively
- B. a SAN extension certificate is used
- C. multiple certificates are used on multiple domains on the same VServer
- D. configuring a content switching SSL VServer with a single domain certificate

Correct Answer: C

QUESTION 2

Scenario: A web server needs to be load-balanced but the content for the web page is retrieved from different server pools. There is a server pool for images, another for text files, and another for documents.

Which NetScaler feature would allow a user to retrieve content from all pools through a single IP address by leveraging the ability of NetScaler to forward traffic based on the incoming request?

- A. Load Balancing
- B. Content Filtering
- C. Content Switching
- D. Global Server Load Balancing

Correct Answer: A

QUESTION 3

Which service setting would a NetScaler Engineer use in the command-line interface to limit connections to server resources?

- A. -maxReq
- B. -maxClient
- C. -monThreshold
- D. -maxBandwidth

Correct Answer: B

QUESTION 4



While binding a certificate key pair where the key is a 2048-bit, a NetScaler Engineer receives the following error message:

"Certificate with key size greater than RSA512 or DSA512 bits not supported"

What could be causing this error?

- A. The certificate being used is invalid.
- B. The license file is saved in UTF-8 format.
- C. The NetScaler does NOT have an SSL offloading card.
- D. The NetScaler appliance does NOT have an appropriate license.

Correct Answer: D

QUESTION 5

Scenario: A network engineer has created and bound an UDP-ECV monitor to identify the status of a UDP service. However, no matter what the response is, the service is always marked as UP.

A possible cause of this behavior is that the network engineer _____. (Choose the correct option to complete the sentence.)

- A. forgot to add a receive string
- B. added the string ns_true as receive string
- C. added a string that is invalid and thus skipped
- D. added a string that is always part of the UDP handshake

Correct Answer: A

[Latest 1Y0-351 Dumps](#)

[1Y0-351 Study Guide](#)

[1Y0-351 Exam Questions](#)