



# 1Y0-402<sup>Q&As</sup>

Citrix XenApp and XenDesktop 7.15 Assessment, Design and Advanced Configurations

## Pass Citrix 1Y0-402 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/1y0-402.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Citrix Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





### QUESTION 1

Scenario: After a recent security assessment, a Citrix Architect recommends blocking unnecessary peripheral types by disabling the associated HDX channels. Currently, the environment is intended to support the peripheral types listed in the Exhibit.

Click the Exhibit button to view the supported peripheral types.

| Allowed Peripherals  | Prohibited Peripherals   |
|--|--|
| <ul style="list-style-type: none"><li>• Keyboard</li><li>• Standard mouse</li><li>• Endpoint drives</li><li>• Webcams</li><li>• Scanners</li></ul> | <ul style="list-style-type: none"><li>• Smart cards</li><li>• Headsets (headphones and microphone)</li><li>• Printers</li><li>• Any additional specialized peripherals that have NOT been approved for inclusion</li></ul> |

Which four HDX virtual channels should the architect disable, based on the peripherals required in the environment? (Choose four.)

- A. SmartCard
- B. TWI
- C. Print
- D. ClientAudio
- E. GenericUSB
- F. TwainRdr
- G. Multimedia

Correct Answer: ACDE

### QUESTION 2

Scenario: A Citrix Architect needs to design a new XenApp and XenDesktop environment. Currently, the environment is configured with two locations with identical XenDesktop Sites. Each Site has two Delivery Controllers, two StoreFront servers, and one NetScaler high availability pair. The same applications have been published from both Sites for all the users. Two Zones (Zone A and Zone B) are configured in each Site with one Controller in each zone. The Microsoft Exchange server is only accessible from Virtual Delivery Agent (VDA) machines in Zone A in each Site.

The following access requirements have been identified:



Users should have a single URL when accessing resources from different Sites.

Users should always connect to the datacenter closest to their location.

Applications added to Favorites within Citrix Receiver should be retained when accessed from different Sites.

Launched applications and desktops should always connect through a local NetScaler.

No duplication of applications published from different Sites.

Microsoft Outlook should always launch in Zone A.

In which mode should the architect recommend configuring Global Server Load Balancing (GSLB) to ensure that a user always connects to the datacenter closest to their location?

- A. Source IP hash
- B. Dynamic RTT
- C. Least response time
- D. Static Proximity

Correct Answer: C

---

### QUESTION 3

A Citrix Architect needs to conduct a capabilities assessment for an organization that wants to design and build a new XenApp and XenDesktop environment.

Which four capabilities will directly influence whether the existing Citrix administrative team will have the capacity to support the new environment? (Choose four.)

- A. Network architecture
- B. Current backup solutions
- C. Users and applications
- D. Existing XenApp and XenDesktop environments
- E. Training and certifications of support staff and users
- F. Current storage solutions
- G. Image management processes

Correct Answer: ACDF

---



#### QUESTION 4

A Citrix Architect needs to conduct a capabilities assessment for an organization that wants to design and build a new XenApp and XenDesktop environment.

Which three capabilities will directly influence whether the existing Citrix administrative team will have the capacity to support the new environment? (Choose three.)

- A. Certificate Authority configuration
- B. Current backup solutions
- C. Users and applications
- D. Image management processes
- E. Training and certifications of support staff and users
- F. DNS infrastructure
- G. Image management processes

Correct Answer: CDF

#### QUESTION 5

Scenario: IT management has decided which server hardware model to use for new XenApp and XenDesktop Sites and needs guidance on sizing the Hardware Layer.

Click the Exhibit to view the host details.

| Host Details     |             |
|------------------|-------------|
| Host Model       | UCS B200 M4 |
| Sockets          | 2           |
| Cores per Socket | 8           |
| RAM              | 320 GB      |
| Hyper Threading  | Enabled     |
| Storage          | SAN storage |

A Citrix Architect is planning to install XenServer 7.x on this host. How many vCPUs will be available to the XenServer host?

- A. 8
- B. 24
- C. 32
- D. 16



Correct Answer: D

[Latest 1Y0-402 Dumps](#)

[1Y0-402 PDF Dumps](#)

[1Y0-402 Practice Test](#)