



# 1Z0-071<sup>Q&As</sup>

Oracle Database 12c SQL

## Pass Oracle 1Z0-071 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/1z0-071.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Oracle  
Official Exam Center

- ⚙ **Instant Download** After Purchase
- ⚙ **100% Money Back** Guarantee
- ⚙ **365 Days** Free Update
- ⚙ **800,000+** Satisfied Customers





### QUESTION 1

Which two statements are true? (Choose two.)

- A. CASE is a function and DECODE is not.
- B. Neither CASE nor DECODE is a function.
- C. All conditions evaluated using CASE can also be evaluated using DECODE.
- D. All conditions evaluated using DECODE can also be evaluated using CASE.
- E. DECODE is a function and CASE is not.
- F. Both CASE and DECODE are functions.

Correct Answer: DE

### QUESTION 2

Examine the data in the ORDERS table:

ORDER_ID	ORDER DATE
1	<null>
2	<null>
3	01-JAN-2019
4	01-FEB-2019
5	01-MAR-2019

Examine the data in the INVOICES table:

INVOICE_ID	ORDER_ID	ORDER DATE
1	1	<null>
2	2	01-JAN-2019
3	3	<null>
4	4	01-FEB-2019
5	5	01-APR-2019

Examine this query:

```
SELECT order_id, order_date FROM orders  
  
INTERSECT  
  
SELECT order_id, order_date FROM invoices;
```



Which two rows will it return?

- A. 3
- B. 2
- C. 1
- D. 5 01-MAR-2019
- E. 4 01-FEB-2019
- F. 3 01-JAN-2019

Correct Answer: CE

---

### QUESTION 3

Examine this query:

```
SELECT SUBSTR (SYSDATE,1,5) `Result` FROM DUAL
```

Which statement is true?

- A. It fails unless the expression is modified to TO\_CHAR(SUBSTR(SYSDATE,1,5))
- B. It fails unless the expression is modified to SUBSTR (TO\_ CHAR(SYSDATE),1,5)
- C. It fails unless the expression is modified to SUBSTR (TO\_ CHAR(TRUNC(SYSDATE)),1,5)
- D. It executes successfully with an implicit data type conversion

Correct Answer: D

---

### QUESTION 4

Which three statements are true about sequences in a single instance Oracle database? (Choose three.)

- A. A sequence's unallocated cached values are lost if the instance shuts down.
- B. A sequence number that was allocated can be rolled back if a transaction fails.
- C. A sequence can only be dropped by a DBA.
- D. A sequence can issue duplicate values.
- E. Sequences can always have gaps.
- F. Two or more tables cannot have keys generated from the same sequence.

Correct Answer: ADE

---



### QUESTION 5

Which two statements are true about single row functions?

- A. CONCAT: can be used to combine any number of values
- B. MOD: returns the quotient of a division operation
- C. CEIL: can be used for positive and negative numbers
- D. FLOOR: returns the smallest integer greater than or equal to a specified number
- E. TRUNC: can be used with NUMBER and DATE values

Correct Answer: CE

[1Z0-071 PDF Dumps](#)

[1Z0-071 VCE Dumps](#)

[1Z0-071 Exam Questions](#)