



200-401^{Q&As}

Managing Industrial Networks with Cisco Networking Technologies
(IMINS)

Pass Cisco 200-401 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/200-401.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

Which two reasons make mesh bonding systems most effective? (Choose two.)

- A. cover wide areas
- B. provide additional strength to floor structures
- C. provide low-impedance noise-equalizing paths
- D. create equipotential grounding systems
- E. most cost-effective approach

Correct Answer: CD

QUESTION 2

You are called upon to troubleshoot connectivity problems to a network device on a production floor. You have used ping and traceroute to verify that you cannot connect to the device from the management network. The network is 209.165.202.128/27 and the device has been given the IP address 209.165.202.158 and mask 255.255.255.224. You have verified that you can reach the device with your computer connected to the same switch as the device. What could be the cause of this problem?

- A. The device is set to the wrong subnet mask.
- B. The device is set to the wrong IP address.
- C. The device has no IP default gateway.
- D. The device is connected to a switchport in the wrong VLAN.

Correct Answer: C

QUESTION 3

What is the leading cause of fiber-optic link failure?

- A. contaminants
- B. crushed fiber
- C. poor testing practices
- D. bad connectors

Correct Answer: A

QUESTION 4



A network administrator has subnetted the 172.16.0.0 network using a subnet mask of 255.255.255.192. A duplicate IP address of 172.16.2.120 has accidentally been configured on a workstation in the network. The technician on the plant floor must assign this workstation a new IP address within that same subnetwork. Which address should be assigned to the workstation?

- A. 172.16.1.80
- B. 172.16.2.80
- C. 172.16.1.64
- D. 172.16.2.64
- E. 172.16.2.127
- F. 172.16.2.128

Correct Answer: B

QUESTION 5

A router is not operating as expected and the network administrator wants to verify that the router booted using the correct IOS image. Which command should be used to determine which IOS is running on the router?

- A. show flash
- B. show version
- C. show memory
- D. show startup-config
- E. show config-register

Correct Answer: B

[200-401 PDF Dumps](#)

[200-401 VCE Dumps](#)

[200-401 Braindumps](#)