



# 201<sup>Q&As</sup>

TMOS Administration

## Pass F5 201 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/201.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by F5 Official  
Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





### QUESTION 1

A BIG-IP system has the following configuration:

\*

SNAT is set to Auto Map

\*

There are two VLANs internal and external

\*

Default route is pointed to the gateway on external VLAN

\*

Self P for internal VLAN is 192.1.1.2

\*

Self IP for external VLAN is 192.1.2.2

\*

Floating IP addresses for internal VLAN is 192.1.1.1

\*

Floating IP addresses for external VLAN is 192.1.2.1

\*

The Virtual Server IP address is 192.1.1.100

Which IP address does the BIG-IP system use first when traffic reaches the servers on the internal VLAN?

A.

192.1.1.100

B.

192.1.2.2

C.

192.1.1.1

D.

192.1.2.1

Correct Answer: C



### QUESTION 2

How is MAC masquerading configured?

- A. Specify the desired MAC address for each VLAN for which you want this feature enabled.
- B. Specify the desired MAC address for each selfIP address for which you want this feature enabled.
- C. Specify the desired MAC address for each VLAN on the active system and synchronize the systems.
- D. Specify the desired MAC address for each floating selfIP address for which you want this feature enabled.

Correct Answer: A

---

### QUESTION 3

Which two can be a part of a pool's definition? (Choose two.)

- A. rule(s)
- B. profile(s)
- C. monitor(s)
- D. persistence type
- E. loadbalancing mode

Correct Answer: CE

---

### QUESTION 4

A BIG-IP Administrator needs to install a HotFix on a standalone BIG-IP device, which has HD1.1 as the Active Boot Location. The BIG-IP Administrator has already re-activated the license and created an UCS archive of the configuration. In which sequence should the BIG-IP Administrator perform the remaining steps?

- A. Install HotFix in HD 1.1, Reboot the BIG-IP device. Install UCS Archive
- B. Install HotFix in HO 1.2, Install base Image in HD 1.2, Activate HD1.2
- C. Install base Image in HD1.2, Install HotFix in HD1.2, Activate HD 1.2
- D. Activate HD 1.2, Install base image in HD 1.2. Install HotFix in HD 1.2

Correct Answer: C

---

### QUESTION 5

During a high-demand traffic event, the BIG-IP Administrator needs to limit the number of new connections per second



allowed to a Virtual Server.

What should the administrator apply to accomplish this task?

- A. An HTTP Compression profile to the Virtual Server
- B. A connection rate limit to the Virtual Server
- C. A connection limit to the Virtual Server
- D. A OneConnect profile to the Virtual Server

Correct Answer: B

[201 PDF Dumps](#)

[201 Practice Test](#)

[201 Braindumps](#)