



201^{Q&As}

TMOS Administration

Pass F5 201 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/201.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by F5 Official
Exam Center

- ⚙ **Instant Download** After Purchase
- ⚙ **100% Money Back** Guarantee
- ⚙ **365 Days** Free Update
- ⚙ **800,000+** Satisfied Customers





QUESTION 1

A BIG-IP device has only LTM and ASM modules provisioned. Both have nominal provisioning level. The BIG-IP Administrator wants to dedicate more resources to the LTM module. The ASM module must remain enabled. Which tmsh command should the BIG-IP Administrator execute to obtain the desired result?

- A. modify/sys provision asm level minimum
- B. modify /sys provision ltm level dedicated
- C. modify /sys provision asm level none
- D. modify /sys provision ltm level minimum

Correct Answer: A

QUESTION 2

A standard virtual server is defined with a pool and a SNAT using automap. All other settings for the virtual server are at defaults. When client traffic is processed by the BIG-IP, what will occur to the IP addresses?

- A. Traffic initiated by the pool members will have the source address translated to a self-IP address but the destination address will not be changed.
- B. Traffic initiated to the virtual server will have the destination address translated to a pool member address and the source address translated to a self-IP address.
- C. Traffic initiated by selected clients, based on their IP address, will have the source address translated to a self-IP address but the destination will only be translated if the traffic is destined to the virtual server.
- D. Traffic initiated to the virtual server will have the destination address translated to a pool member address and the source address translated to a self-IP address. Traffic arriving destined to other destinations will have the source translated to a self-IP address only.

Correct Answer: B

QUESTION 3

A BIG-IP Administrator defines a device Self IP . The Self IP is NOT reachable from the network. What should the BIG-IP Administrator verify first?

- A. The correct interface has been selected.
- B. The correct VLAN has been selected.
- C. Verify if auto last hop is disabled.
- D. The correct Trunk has been selected.



Correct Answer: B

QUESTION 4

For a given Virtual Server, the BIG-IP must perform SSL Offload and negotiate secure communication over TLSv1.2 only.

What should the BIG-IP Administrator do to meet this requirement?

- A. Configure a custom SSL Profile (Client) and select no TLSv1 in the options list
- B. Configure a custom SSL Profile (Client) with a custom TLSV1.2 cipher string
- C. Configure a custom SSL Profile (Server) and select no TLSv1 in the options list
- D. Configure a custom SSL Profile (Server) with a custom TLSV1.2 cipher string

Correct Answer: B

no TLSv1 only disables TLS1.0, TLS1.1 is still used and does not meet the requirements.

QUESTION 5

Which type of Virtual Server requires the use of a FastL4 profile?

- A. Performance (Layer 4)
- B. Stateless
- C. Performance (HTTP)
- D. Standard

Correct Answer: A

[Latest 201 Dumps](#)

[201 PDF Dumps](#)

[201 Exam Questions](#)