



299-01^{Q&As}

Riverbed Certified Solutions Professional - Network Performance Management

Pass Riverbed 299-01 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/299-01.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Riverbed
Official Exam Center

- ⚙ **Instant Download** After Purchase
- ⚙ **100% Money Back** Guarantee
- ⚙ **365 Days** Free Update
- ⚙ **800,000+** Satisfied Customers





QUESTION 1

What report on Cascade Profiler would be used to show both sides of a conversation and the ports they communicated on?

- A. Peers
- B. Peers and Ports
- C. Host Pairs
- D. Ports
- E. Host Pairs and Ports

Correct Answer: E

QUESTION 2

When working with capture job traces on a Cascade Shark appliance from Cascade Pilot: A. Views should always be applied directly to the job trace.

- B. Trace clips should first be created, and views applied to them.
- C. Packets should be exported from the capture job trace before beginning analysis.
- D. The capture job trace should first be indexed by right-clicking on it and selecting "Index".

Correct Answer: B

QUESTION 3

If a prospective customer has 2000 users what would be a reasonable estimated number of flows per minute used in sizing Profiler?

- A. 2000
- B. 4000
- C. 20000
- D. 40000
- E. 200000
- F. 400000

Correct Answer: D

**QUESTION 4**

If a VLAN SPAN (VLAN101) is configured and monitored by Cascade Shark, which of the following is true? (Select 2)

- A. Inter VLAN101 traffic will be monitored; Intra VLAN101 traffic will not.
- B. Intra VLAN101 traffic will be monitored; Inter VLAN101 traffic will not.
- C. Both inter and intra VLAN101 traffic will be monitored.
- D. It is a best practice to configure the Cascade Shark monitoring port (the SPAN destination) with '\\deduplication\\' enabled.
- E. It is a best practice to configure the Cascade Shark monitoring port (the SPAN destination) without '\\deduplication\\' enabled.

Correct Answer: CD

QUESTION 5

On Cascade Profiler, can you run a traffic report that shows all traffic from inside the network to outside the network, but excludes a proxy server?

- A. No, this cannot be done with Cascade.
- B. Set up the query to ask for all hosts between: Hosts "Within" a group "ByInternalHosts: All" (where All is a host grouping containing all inside address space) and for Peers set to "Outside of. ByInternalHosts:All".
- C. Configure query as B above but also add the Proxy Server to the "Outside" list.
- D. Configure query as B above but also add the Proxy Server as a "not" in the Traffic Expression field. The expression to add would be "not host proxyhost " where proxyhost is the IP Address of the proxy.

Correct Answer: D

[Latest 299-01 Dumps](#)

[299-01 PDF Dumps](#)

[299-01 Braindumps](#)