



2V0-621D^{Q&As}

VMware Certified Professional 6 – Data Center Virtualization Delta

Pass VMware 2V0-621D Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/2v0-621d.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by VMware
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

Which three parameters should be considered when calculating the bandwidth for vSphere Replication? (Choose three.)

- A. Data change rate
- B. Traffic rates
- C. Link speed
- D. Application type
- E. Hardware type

Correct Answer: ABC

Reference: <http://blogs.vmware.com/smb/2015/05/vsphere-replication-bandwidth-requirements.html>

QUESTION 2

What are two likely causes for a DRS cluster to become unbalanced? (Choose two.)

- A. Migration threshold is too low.
- B. Affinity rules are preventing virtual machines from being moved.
- C. A device is mounted to a virtual machine preventing vMotion.
- D. Migration cost is too low.

Correct Answer: BC

Reference: <https://pubs.vmware.com/vsphere-51/index.jsp?topic=%2Fcom.vmware.vsphere.troubleshooting.doc%2FUG-0C132C85-E7BF-445E-925D-31420A06B01C.html>

QUESTION 3

An administrator tries to capture network traffic for a virtual machine, but cannot see the expected traffic in the packet capture tool. Which step can resolve the problem?

- A. Migrate the virtual machine to a Distributed Virtual Switch.
- B. Enable Promiscuous Mode on the relevant port group.
- C. Modify the default value of MAC Address changes.
- D. Enable Forged Transmits on the virtual machine.

Correct Answer: B



Although it is not a good practice to enable promiscuous mode on a distributed virtual switch, you can enable it to solve the problem of traffic stats in packet capture tool.

QUESTION 4

An administrator is upgrading an ESXi host from 5.5 to 6.0 and runs the following command:

```
esxcli software vib list -rebooting-image
```

What does this command show?

- A. VIBs active after a reboot.
- B. VIBs that require a reboot.
- C. VIBs that are in the boot image.
- D. VIBs that are third-party.

Correct Answer: A

The command shows that the VIBs are active after a reboot.

QUESTION 5

An administrator is performing a silent automatic update of VMware Tools on a Windows virtual machine. What syntax needs to be entered into the Advanced Options box?

- A. /s /v "/qn" /l "c:\Windows\filename.log"
- B. --prefix=/usr/local,/usr/lib,/usr/doc --silent
- C. --prefix=c:\Windows,c:\VMtools --silent
- D. /fs /v "/qn+" /l "c:\Windows\filename.log"

Correct Answer: A

One way to determine the component values to use is to run the interactive VMware Tools installer with full logging turned on, select the components that you want installed, and then search the log files for the ADDLOCAL and REMOVE properties. The log files show the names used by the program.

Reference: http://pubs.vmware.com/vsphere-50/advanced/print.jsp?topic=/com.vmware.vsphere.additional_resources.doc_50/GUID-3D2186A2-6EC7-470E-8D1E-CA226EDBBBB0.html