



# 300-430<sup>Q&As</sup>

Implementing Cisco Enterprise Wireless Networks (ENWLSI)

## Pass Cisco 300-430 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/300-430.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco  
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





### QUESTION 1

An engineer has been hired to implement a way for users to stream video content without having issues on the wireless network. To accomplish this goal, the engineer must set up a reliable way for a Media Stream to work between Cisco FlexConnect APs. Which feature must be enabled to guarantee delivery?

- A. Multicast-Unicast Direct
- B. Multicast Direct
- C. Unicast Direct
- D. IGMP Direct

Correct Answer: B

---

### QUESTION 2

An administrator is querying the Cisco CMX server through REST API for active client data to build an application. Cisco CMX supports the use of version 3 of REST API to query for active clients in the network. While testing to retrieve information using the API, no results are received. Which configuration is required for authentication against the API?

- A. cmxos v3 apiserver user add
- B. cmxos apiserver user add
- C. cmxctl apiserver user add
- D. cmxctl v3 apiserver user add

Correct Answer: A

---

### QUESTION 3

An engineer set up a local authenticated Cisco FlexConnect AP with a guest LAN. Guests report not being able to authenticate. Which configuration must be changed on the WLAN for guests to be able to authenticate?

- A. AAA override
- B. RADIUS NAC
- C. central authentication
- D. backup RADIUS server

Correct Answer: C

---

### QUESTION 4



During the EAP process and specifically related to the client authentication session, which encrypted key is sent from the RADIUS server to the access point?

- A. WPA key
- B. session key
- C. encryption key
- D. shared-secret key

Correct Answer: B

---

#### QUESTION 5

An administrator receives reports of many interferences in the wireless network and wants to get these interferences' location from the maps in Cisco Prime Infrastructure. When looking at the floor plans/maps, the administrator does not see any interferences but can see all wireless clients located successfully. What must be configured to get the location?

- A. Add MSE to Cisco Prime Infrastructure and synchronized.
- B. Enable interferer tracking on the MSE.
- C. Activate NMSP communication with the WLC.
- D. Configure SNMP between Cisco Prime Infrastructure and the WLC.

Correct Answer: B

[Latest 300-430 Dumps](#)

[300-430 Practice Test](#)

[300-430 Exam Questions](#)