



# 300-430<sup>Q&As</sup>

Implementing Cisco Enterprise Wireless Networks (ENWLSI)

## Pass Cisco 300-430 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/300-430.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco  
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





### QUESTION 1

An engineer is in the process of implementing Fastlane on a wireless network with a Mobility Express AP installed and Apple end-user devices. Due to a security concern, the IT department has updated all the iPads to version 14.5.423551943. Which QoS profile must the engineer configure on the user WLAN?

- A. Platinum
- B. Best Effort
- C. Bronze
- D. Silver

Correct Answer: A

---

### QUESTION 2

An engineer is managing a wireless network for a shopping center. The network includes a Cisco WLC, a Cisco MSE, and a Cisco Prime Infrastructure. What is required to use Cisco CMX Location Analytics?

- A. Enable tracking parameters in Cisco MSE.
- B. Enable Context Aware and CMX Browser Engage.
- C. Install Cisco Prime Infrastructure with floor maps.
- D. Set history parameters in Cisco MSE.

Correct Answer: C

[https://www.cisco.com/c/en/us/td/docs/wireless/mse/10-6/cmxc\\_config/b\\_cg\\_cmxc106/getting\\_started\\_with\\_cisco\\_cmxc.html](https://www.cisco.com/c/en/us/td/docs/wireless/mse/10-6/cmxc_config/b_cg_cmxc106/getting_started_with_cisco_cmxc.html)

---

### QUESTION 3

A wireless engineer has performed a Wireshark capture on an 802.1x authentication process to troubleshoot a connectivity issue. Which two types of packet does the EAP contain? (Choose two.)

- A. EAP complete
- B. EAP response
- C. EAP failure
- D. EAP request
- E. EAP reply

Correct Answer: BD

---



#### QUESTION 4

A network engineer is configuring a Cisco AireOS WLC environment for central web authentication using Cisco ISE.

The controllers are configured using auto-anchor for the guest network.

Which three components must be implemented for the foreign WLC?(Choose three.)

- A. DHCP RADIUS profiling enabled.
- B. HTTP RADIUS profiling enabled.
- C. UDP/1812-1813 open to ISE
- D. downloadable preauth ACL on ISE
- E. local preauth ACL on WLC
- F. WLAN Layer 2 security

Correct Answer: ACF

---

#### QUESTION 5

The security policy mandates that only controller web management traffic is allowed from the IT subnet. In testing, an engineer is trying to connect to a WLAN with Web Authentication for guest users, but the page is timing out on the wireless

client browser.

What is the cause of this issue?

- A. Web Authentication Redirect is supported only with Internet Explorer, and the client is using Google Chrome.
- B. The DNS server that is configured on the controller is incorrect
- C. Web Authentication Redirect is not supported with CPUACLs. QUE
- D. The implemented CPU ACL on the controller is blocking HTTP/HTTPS traffic from the guest clients.

Correct Answer: D

[Latest 300-430 Dumps](#)

[300-430 Study Guide](#)

[300-430 Exam Questions](#)