



300-625^{Q&As}

Implementing Cisco Storage Area Networking (DCSAN)

Pass Cisco 300-625 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/300-625.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

DRAG DROP

Drag and drop the DCNM configuration tasks from the left onto the correct tools on the right.

Select and Place:

- View the values for more than one switch at a time.
- Display fabric extenders.
- Configure vFC interfaces.
- Use the End to End Connectivity Analysis tool to verify connections.
- Configure zones for multiple VSANs.

Device Manager

[Empty box]

[Empty box]

[Empty box]

Cisco DCNM-SAN Client

[Empty box]

[Empty box]

Correct Answer:



Device Manager

- Configure vFC interfaces.
- Configure zones for multiple VSANs.
- View the values for more than one switch at a time.

Cisco DCNM-SAN Client

- Use the End to End Connectivity Analysis tool to verify connections.
- Display fabric extenders.

QUESTION 2

Which configuration is always required when running the setup utility on a Cisco MDS 9000 Series Switch?

- A. administrator password
- B. management IP address
- C. active NTP server
- D. active default gateway

Correct Answer: A

QUESTION 3

Refer to the exhibit.



```
MDS-A# show run
...
!Activate Zone Database Section for vsan 10
zone name Server11 vsan 10
  member pwnn 11:11:11:11:11:11:11:11
  member pwnn 11:11:11:11:11:11:11:12
zoneset name Zoneset10-A vsan 10
  member Server11
zoneset activate name Zoneset10-A vsan 10
...

MDS-B# show run
...
!Activate Zone Database Section for vsan 10
zone name Server11 vsan 10
  member pwnn 11:11:11:11:11:11:11:11
  member pwnn 11:11:11:11:11:11:11:12
  member pwnn 11:11:11:11:11:11:11:13
zoneset name Zoneset10-B vsan 10
  member Server11
zoneset activate name Zoneset10-B vsan 10
...

MDS-A# show interface fc1/11
fc1/11 is trunking (Not All VSANs UP on the trunk)
  Port description is *** ISL-Trunk-MDS-B ***
  ....
  Port mode is TE
  Port vsan is 20
  ....
  Trunk vsans (admin allowed and active) (10,20)
  Trunk vsans (up) (20)
  Trunk vsans (isolated) (10)
  Trunk vsans (initializing) ()
  ...

MDS-A# show log
...
... MDS-A %ZONE-2-ZS_MERGE_FULL_DATABAE_MISMATCH: %SVSAN 10%S Zone merge full database
mismatch on interface fc1/11
... MDS-A %ZONE-2-ZS_MERGE_FAILED: %SVSAN 10%S Zone merge failure, isolating interface
fc1/11 reason: Member mismatch:[reason:0]
... MDS-A %PORT-5-IF_TRUNK_DOWN: %SVSAN 10%S Interface fc1/11, vsan 10 is down
(Isolation due to zone merge failure) *** ISL-Trunk-MDS-B FC1/11 ***
```

A storage network engineer gets remote access to two Cisco MDS 9000 Series Switches with an ISL trunk and receives several log messages. Which set of actions resolve the problem while least affecting service?

- A. 1. Add :11:11:11:11:11:11:11:13 pwnn in zone Server11 and activate Zoneset10-A on MDS-A.
- 2. shut/no shut interface fc1/11 on MDS-A.
- B. 1. Deactivate zone set Zoneset10-A on MDS-A.
- 2. shut/no shut interface fc1/11 on MDS-A.
- C. 1. Add :11:11:11:11:11:11:13 pwnn in zone Server11 and activate Zoneset10-A on MDS-A.
- 2. Remove VSAN 10 from the allowed VSAN range of interface fc1/11 on MDS-A and add it back in the range.



- D. 1. Explicitly import zone set Zoneset10-A on MDS-B using the zoneset import interface import fc1/11 vsan 10 command.
2. Activate the zone set Zoneset10-A.

Correct Answer: A

QUESTION 4

After user account attributes are modified in Cisco NX-OS, when do changes to the user's session attributes take effect?

- A. immediately
- B. at the scheduled time
- C. when the user logs out of a session
- D. when the user creates a new session

Correct Answer: D

QUESTION 5

A Cisco MDS Series Switch with the POAP feature boots and does not find the startup configuration. Which location is checked first when the switch enters POAP mode?

- A. USB device that contains the software image files and the switch configuration file
- B. DHCP server to bootstrap the interface IP address, gateway, DNS server, and TFTP IP addresses
- C. TFTP server where the necessary configuration files are downloaded
- D. HTTP server where the URL is used to download the software image

Correct Answer: A

[300-625 VCE Dumps](#)

[300-625 Exam Questions](#)

[300-625 Braindumps](#)