



300-625^{Q&As}

Implementing Cisco Storage Area Networking (DCSAN)

Pass Cisco 300-625 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/300-625.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco
Official Exam Center

- ⚙ **Instant Download** After Purchase
- ⚙ **100% Money Back** Guarantee
- ⚙ **365 Days** Free Update
- ⚙ **800,000+** Satisfied Customers





QUESTION 1

DRAG DROP

Drag and drop the boot issues from the left onto the correct solutions on the right.

Select and Place:

The BIOS is corrupted.	Replace the module.
The bootflash is corrupted.	Specify the entire path.
Boot parameters are incorrect.	Use the netboot option.
The Cisco NX-OS image is corrupted.	Recover by using the boot loader.

Correct Answer:

	The BIOS is corrupted.
	Boot parameters are incorrect.
	The bootflash is corrupted.
	The Cisco NX-OS image is corrupted.

QUESTION 2

A storage engineer is troubleshooting a Cisco MDS switch upgrade issue. What prevents the completion of a non-disruptive upgrade?

- A. The Fibre Channel host initiator is connected.
- B. The Fibre Channel storage target is connected.



- C. The Cisco Fabric Services operation in progress.
- D. The Fibre Channel and FCoE storage targets are connected.

Correct Answer: B

Reference: https://www.cisco.com/en/US/docs/storage/san_switches/mds9000/sw/rel_3_x/release/notes/14116.16.html

QUESTION 3

DRAG DROP

Drag and drop the mechanisms of Cisco Secure Boot from the left into the correct order on the right.

Select and Place:

Validate the Cisco digital signature on the next set of instructions.	Step 1
The operating system is launched if all the checks are passed.	Step 2
The microloader instruction set is stored in a genuine hardware anchor.	Step 3
Validate the genuineness of the device operating system.	Step 4

Correct Answer:

	The microloader instruction set is stored in a genuine hardware anchor.
	Validate the Cisco digital signature on the next set of instructions.
	Validate the genuineness of the device operating system.
	The operating system is launched if all the checks are passed.

QUESTION 4



Which configuration is always required when running the setup utility on a Cisco MDS 9000 Series Switch?

- A. administrator password
- B. management IP address
- C. active NTP server
- D. active default gateway

Correct Answer: A

QUESTION 5

A storage administrator manually configures a storage switch to use a new static domain ID. After issuing an fcdomain restart vsan 1 command, the administrator sees that the switch is still using the existing domain ID. What is the reason why the configuration is not working?

- A. Static domain IDs apply only after a switch is rebooted.
- B. The disruptive keyword was not used on the command.
- C. Build fabric notifications were not sent to the other switches.
- D. Domain manager fast restart is not enabled on the switch.

Correct Answer: A

[300-625 PDF Dumps](#)

[300-625 Study Guide](#)

[300-625 Exam Questions](#)