



300-715^{Q&As}

Implementing and Configuring Cisco Identity Services Engine (SISE)

Pass Cisco 300-715 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/300-715.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

When configuring Active Directory groups, what does the Cisco ISE use to resolve ambiguous group names?

- A. MIB
- B. TGT
- C. OMAB
- D. SID

Correct Answer: D

QUESTION 2

An engineer wants to preselect AD groups to be used in the access policy after integrating Cisco ISE with an active directory. Which configuration steps must the engineer take to assign groups to the AD on the identity management page?

- A. external identity sources > active directory > groups
- B. user identity groups > groups
- C. external identity sources > groups > active directory
- D. groups > user identity groups

Correct Answer: A

QUESTION 3

An administrator is migrating device administration access to Cisco ISE from the legacy TACACS+ solution that used only privilege 1 and 15 access levels. The organization requires more granular controls of the privileges and wants to customize access levels 2-5 to correspond with different roles and access needs. Besides defining a new shell profile in Cisco ISE.

What must be done to accomplish this configuration?

- A. Enable the privilege levels in Cisco ISE
- B. Enable the privilege levels in the IOS devices.
- C. Define the command privileges for levels 2-5 in the IOS devices
- D. Define the command privileges for levels 2-5 in Cisco ISE

Correct Answer: B



<https://learningnetwork.cisco.com/s/blogs/a0D3i000002eeWTEAY/cisco-ios-privilege-levels>

QUESTION 4

A policy is being created in order to provide device administration access to the switches on a network. There is a requirement to ensure that if the session is not actively being used, after 10 minutes, it will be disconnected.

Which task must be configured in order to meet this requirement?

- A. session timeout
- B. idle time
- C. monitor
- D. set attribute as

Correct Answer: A

https://www.cisco.com/c/en/us/td/docs/security/ise/2-4/admin_guide/b_ISE_admin_guide_24/m_admin_accesspolicy_settings.html#reference_0E24B8FB_FAB248219E1194435670347F

QUESTION 5

Due to a recent network incident, all access to network devices must be centrally logged and tracked in Cisco ISE. On which nodes must the Device Admin service be enabled?

- A. one PAN
- B. each PSN
- C. each PAN
- D. one PSN

Correct Answer: B

[Latest 300-715 Dumps](#)

[300-715 Study Guide](#)

[300-715 Brindumps](#)