



350-401^{Q&As}

Implementing and Operating Cisco Enterprise Network Core Technologies (ENCOR) & CCIE Enterprise Infrastructure & CCIE Enterprise Wireless





Pass Cisco 350-401 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/350-401.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

Refer to the exhibit.

```
R2(config)#event manager applet script_1
R2(config-applet)#action 1 cli command "enable"
R2(config-applet)#action 2 cli command "config t"
R2(config-applet)#action 3 cli command "interface ge0/0"
R2(config-applet)#action 4 cli command "ip add 172.16.1.1 255.255.255.0"
R2(config-applet)#action 5 cli command "no sh"
R2(config-applet)#action 6 cli command "end"
R2(config-applet)#exit
```

An engineer must create a manually triggered EEM applet to enable the R2 router interface and assign an IP address to it. What is required to complete this configuration?

- A. R2(config-applet)# event oir
- B. R2(config-applet)#action 4 cli command "ip add 172.16.1.1 0.0.0.255"
- C. R2(config)# event manager session cli username
- D. R2(config-applet)# event none sync yes

Correct Answer: D

QUESTION 2

SIMULATION

Task

Configure HSRP between DISTRO-SW1 and DISTRO-SW2 on VLAN 100 for hosts connected to ACCESS-SW1 to achieve these goals:

1.
Configure group number 1 using the virtual IP address of 192.168.1.1/24.
2.
Configure DISTRO-SW1 as the active router using a priority value of 110 and DISTRO-SW2 as the standby router.
3.
Ensure that DISTRO-SW2 will take over the active role when DISTRO-SW1 goes down, and when DISTRO-SW1



recovers, it automatically resumes the active role.

Topology

Remote access must be arranged via third-party solutions.

Remote access requires an Internet connection only.

This model is cost-effective.

This model is high-maintenance and has high operating costs.

Cloud

On-Premises



Cloud

Remote access must be arranged via third-party solutions.

This model is cost-effective.

On-Premises

Remote access requires an Internet connection only.

This model is high-maintenance and has high operating costs.



```
import   
  
data = {  
    "measurement": "freeMemory",  
    "maxDataPoints": 30,  
    "alert": True,  
    "policy": "1.2.1",  
    "devices": [{"model": "Cisco 2921 ISR", "ipv4": '10.10.10.1'}]  
}  
model = data["devices"][0]["model"]  
  
json_string =  (data)  
  
print(  )
```

model

json

json.dumps

json.loads

json_string

DISTRO-SW2



```
import json

data = {
    "measurement": "freeMemory",
    "maxDataPoints": 30,
    "alert": True,
    "policy": "1.2.1",
    "devices": [{"model": "Cisco 2921 ISR", "ipv4": '10.10.10.1'}]
}
model = data["devices"][0]["model"]

json_string = json.dumps(data)

print(json_string)
```

model

json.loads

```
import json

data = {
    "measurement": "cefcFRUPowerOperStatus",
    "maxDataPoints": 45,
    "alert": "True",
    "errorDescription": None,
    "devices": [{"model": "Cisco 4331 ISR"}, {"model": "Cisco 3500 S"}]
}

obj = json.{}.{}.{}

print(obj)
```

JSONEncoder

data

decode

.encode

JSONDecoder

A. See the solution below in Explanation.

B. Place Holder

C. Place Holder



D. Place Holder

Correct Answer: A

DISTRO-SW1 Sw1 int vlan 100 standby 1 ip 192.168.1.1 standby 1 priority 110 standby 1 preempt copy run start

DISTRO-SW2 SW2 int vlan 100 standby 1 ip 192.168.1.1 standby 1 preempt copy run start

OR

MINOR CHANGE IN ABOVE HSRP SCENERIO

```
import json

data = {
    "measurement": "cefcFRUPowerOperStatus",
    "maxDataPoints": 45,
    "alert": "True",
    "errorDescription": None,
    "devices": [{"model": "Cisco 4331 ISR"}, {"model": "Cisco 3500 S"}]
}

obj = json.JSONEncoder().encode(data)

print(obj)
```

DISTRO-SW1 Sw1

int vlan 100 glbp 1 ip 192.168.1.254 glbp 1 priority 110 glbp 1 timers 5 15 glbp 1 preempt

copy run start

DISTRO-SW2 SW2 int vlan 100 glbp 1 ip 192.168.1.254 glbp 1 timers 5 15 glbp 1 preempt copy run start

QUESTION 3

What is a characteristic of Cisco StackWise technology?

- A. It uses proprietary cabling
- B. It supports devices that are geographically separated
- C. It combines exactly two devices
- D. It is supported on the Cisco 4500 series.



Correct Answer: A

Reference: <https://www.cisco.com/c/en/us/products/collateral/switches/catalyst-9200-series-switches/nb-06-stackwise-architecture-cte-en.html>

QUESTION 4

Which there application has the ability to make REST calls against Cisco DNA Center?

- A. API Explorer
- B. REST Explorer
- C. Postman
- D. Mozilla

Correct Answer: C

QUESTION 5

Which two statements about EIGRP load balancing are true? (Choose two)

- A. Cisco Express Forwarding is required to load-balance across interfaces
- B. A path can be used for load balancing only if it is a feasible successor
- C. EIGRP supports unequal-cost paths by default
- D. Any path in the EIGRP topology table can be used for unequal-cost load balancing
- E. EIGRP supports 6 unequal-cost paths

Correct Answer: BE

EIGRP provides a mechanism to load balance over unequal cost paths (or called unequal cost load balancing) through the "variance" command. In other words, EIGRP will install all paths with metric

[Latest 350-401 Dumps](#)

[350-401 PDF Dumps](#)

[350-401 Exam Questions](#)