



350-701^{Q&As}

Implementing and Operating Cisco Security Core Technologies (SCOR)

Pass Cisco 350-701 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/350-701.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

What is a characteristic of a bridge group in ASA Firewall transparent mode?

- A. It includes multiple interfaces and access rules between interfaces are customizable
- B. It is a Layer 3 segment and includes one port and customizable access rules
- C. It allows ARP traffic with a single access rule
- D. It has an IP address on its BVI interface and is used for management traffic

Correct Answer: A

Reference:

<https://www.cisco.com/c/en/us/td/docs/security/asa/asa95/configuration/general/asa-95-generalconfig/intro-fw.html>

Note: BVI interface is not used for management purpose. But we can add a separate Management slot/port interface that is not part of any bridge group, and that allows only management traffic to the ASA.

QUESTION 2

What are two benefits of Flexible NetFlow records? (Choose two)

- A. They allow the user to configure flow information to perform customized traffic identification
- B. They provide attack prevention by dropping the traffic
- C. They provide accounting and billing enhancements
- D. They converge multiple accounting technologies into one accounting mechanism
- E. They provide monitoring of a wider range of IP packet information from Layer 2 to 4

Correct Answer: AD

Reference:

https://www.cisco.com/en/US/docs/ios/fnetflow/configuration/guide/cust_fnflow_rec_mon_external_docbase_0900e4b18055d0d2_4container_external_docbase_0900e4b181b413_d9.html#wp1057997Note: Traditional NetFlow allows us to

monitor from Layer 2 to 4 but Flexible NetFlow goes beyond these layers.

QUESTION 3

An engineer is adding a Cisco DUO solution to the current TACACS+ deployment using Cisco ISE. The engineer wants to authenticate users using their account when they log into network devices. Which action accomplishes this task?

- A. Configure Cisco DUO with the external Active Directory connector and tie it to the policy set within Cisco ISE.



- B. Install and configure the Cisco DUO Authentication Proxy and configure the identity source sequence within Cisco ISE
- C. Create an identity policy within Cisco ISE to send all authentication requests to Cisco DUO.
- D. Modify the current policy with the condition MFASourceSequence DUO=true in the authorization conditions within Cisco ISE

Correct Answer: B

<https://community.cisco.com/t5/security-documents/duo-mfa-integration-with-ise-for-tacacsdevice-administration/tap/3881767>

QUESTION 4

An administrator is configuring NTP on Cisco ASA via ASDM and needs to ensure that rogue NTP servers cannot insert themselves as the authoritative time source Which two steps must be taken to accomplish this task? (Choose two)

- A. Specify the NTP version
- B. Configure the NTP stratum
- C. Set the authentication key
- D. Choose the interface for syncing to the NTP server
- E. Set the NTP DNS hostname

Correct Answer: CD

QUESTION 5

Which command is used to log all events to a destination collector 209.165.201.10?

- A. CiscoASA(config-pmap-c)# flow-export event-type all destination 209.165.201.10
- B. CiscoASA(config-cmap)# flow-export event-type flow-update destination 209.165.201.10
- C. CiscoASA(config-pmap-c)# flow-export event-type flow-update destination 209.165.201.10
- D. CiscoASA(config-cmap)# flow-export event-type all destination 209.165.201.10

Correct Answer: A

Reference:

https://www.cisco.com/c/en/us/td/docs/security/asa/asa84/configuration/guide/asa_84_cli_config/monitor_nsel.html