



3605^{Q&As}

Avaya Ethernet Routing Switch Implementation and Maintenance Exam

Pass Avaya 3605 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/3605.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Avaya
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

The trace level 9 3 command accomplish?

- A. It captures BGP events at a terse level.
- B. It captures packets copied to the CPU at a verbose level.
- C. It shows CPU utilization.
- D. It captures RCC IP events at verbose level.

Correct Answer: B

QUESTION 2

With release 4.0 or higher software on the Ethernet routing switch (ERS) 8300, an advanced routing license is required to enable certain features. Which two statements are true about the Advanced Routing License process and supported features for the ERS 8300? (Choose two.)

- A. the Advanced Routing License supports QoS, SMLT, VRRP and OSPF
- B. the Advanced Routing License supports SMLT, VRRP, OSPF, PIM-SM. and SLPP
- C. To protect against security breaches, the ERS 8300 allows only a primary path for the license file
- D. To protect against system flash failure, the ERS 8300 allows a primary, secondary, and tertiary path for the license file.

Correct Answer: BD

QUESTION 3

Which statement describe step in provisioning SPBM in an Enterprise network?

- A. IP addresses on the core links.
- B. Enable SPBM and IS-IS globally on all nodes and on the core facing links.
- C. Configure the MAC table.
- D. Configure L2 and L3 VSNs on the core SPBM nodes.

Correct Answer: B

QUESTION 4

A technician has implemented Routed Split Multi-Link Trunking (RSMLT) edge design. After recovering power outage some clients could not communicate. It has



been determined that only one of the core RSMLT switches has recovered.

What should have been done to prevent the loss communications?

- A. Turn off the HoldDown timer.
- B. Increase the Holdup timer to 9999.
- C. Clear the peer IP and MAC addresses
- D. Set the VLAN to copy RSMLT info from a similarly configured VLAN.

Correct Answer: B

QUESTION 5

A technician wants to use the New Unit Quick Configuration feature to add new units to a stack of Ethernet Routing Switch (ERS) 5000 switches without. As well as enabling the feature, what else must be done to use the New Unit Quick Communication feature?

- A. Save a template on the base unit
- B. Save a template on the backup unit
- C. Insert a new switch in the stack
- D. Apply the feature license

Correct Answer: C

[3605 Practice Test](#)

[3605 Study Guide](#)

[3605 Braindumps](#)