



# 3605<sup>Q&As</sup>

Avaya Ethernet Routing Switch Implementation and Maintenance Exam

## Pass Avaya 3605 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/3605.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Avaya  
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





### QUESTION 1

In the interaction between EAPO17802.1 and the Enterprise Policy Manager (EPM), what is the role EPM in the User-Based Policy (UBP) process?

- A. It passes the user access request to the RADIUS server
- B. It authenticates the user request.
- C. It opens a port.
- D. it applies the required treatment to the access port.

Correct Answer: A

---

### QUESTION 2

When Incorporating Split Multi-Link Trunk (SMLT) on a pair of Ethernet Routing Switch (ERS) 8600 switches traffic from the edge of the network is directed to

either ERS 8600. The ping-snoop feature assists in determining which path the traffic is taking.

How does the ping-snoop operation work?

- A. Ping snoop requires configuration changes to the edge devices.
- B. Ping snoop looks at the MAC header and directs traffic to the designated link.
- C. Ping snoop identifies traffic that matches the IP flow specified in the ping snoop command.
- D. Ping snoop configurations are saved and can be configured to restart automatically after a reboot.

Correct Answer: C

---

### QUESTION 3

When configuring an Ethernet Routing Switch (ERS) 8600 for Split Multi link Trunking (SMLT). Protection against an edge switch in the factory default condition must be taken into consideration. Which parameter WILL help prevent loops on the SMLT ports?

- A. Discard Untagged Frames
- B. Discard Looped Frames
- C. Spanning Tree Enable
- D. LACP Enable

Correct Answer: A

---



#### QUESTION 4

A technician has compiled the configuration of an Ethernet Routing (ERS) 5520 to and now must transfer a backup copy of configuration file to server. Which command is used to accomplish this task?

- A. 5520.24T-PWR> copy config ftp filename ers5520 config.cfg
- B. 5520-24T-PWR# copy config ftp filename ers5520config.cfg
- C. 5570-74T PWR# copy config tftp filename ers5520COnfig.cfg
- D. 5520-24T-PWR# copy config scp filename ersS520conftg.cfg

Correct Answer: C

---

#### QUESTION 5

A technician needs to reboot an Ethernet Routing Switch (ERS) 5000 Series switch with a default configuration. What needs to be done to keep the IP address and stack license?

- A. Boot partial-default
- B. Boot-default save-license
- C. Boot default-save
- D. Boot restore-license

Correct Answer: A

[3605 PDF Dumps](#)

[3605 VCE Dumps](#)

[3605 Braindumps](#)