



# 3605<sup>Q&As</sup>

Avaya Ethernet Routing Switch Implementation and Maintenance Exam

## Pass Avaya 3605 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/3605.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Avaya  
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





### QUESTION 1

A technician is adding the Virtual Link Aggregation Control Protocol (VLACP) configuration ID a Converged Campus Solution where all Ethernet Routing switches

(ERSs) are directly connected without intermediary WAN transport devices.

What are two key configuration tasks? (Choose two)

- A. configure all links to use the default multicast MAC address for VLACP messages
- B. For the 1ST links, configure the long timeout value
- C. For the SMLT links, configure the long timeout value
- D. Configure all links to use a unique reserved multicast MAC address for VLACP messages

Correct Answer: BD

---

### QUESTION 2

An Ethernet routing switch (ERS) 4550T-PWR has been deployed with a single AC power supply and is currently supporting 20 VoIP telephones with power over Ethernet (PoE). each with a power draw of 8 Watts when offhook. The network engineer has requested the addition of 5 Wireless Access points (WAPs) to the ERS 4550T-PWR. Each WAP supports PoE and requires 12 Watts of power.

What is the outcome of the addition of the WAPs to the ERS 4550T-PWR?

- A. The 4550T-PWR will have sufficient power to support the 20 VoIP telephones and 5 WAP devices,
- B. The addition of a second AC power supply will be required to provide sufficient power to the ERS -4550T-PWR to Support all of-the PoE devices.
- C. The addition of a Redundant Power Supply 15 will be required to provide sufficient power to ensure the VoIP phones and WAP function property.
- D. the power requirement of the WAP exceeds the individual port maximum power rating of the ERS 4550T-PWR and will therefore require an external power source.

Correct Answer: A

---

### QUESTION 3

The Ethernet Routing Switch (ERS) 8600 supports the feature IP VPN-Lite that does not require the use of an MPLS network. Which function does the ERS 8600 as a Provider Edge (PE) perform for IP VPN-Lite?'

- A. The PE uses the Virtual Routing Forwarding (VRF) instances to provide traffic separation.
- B. The PE provides route exchange with remote PE devices using OSPF.
- C. The PE adds a shim header to the Ethernet header specifying which network the packet is crossing.



D. The PE incorporates Label Distribution Protocol across the core network to connect remote PE devices.

Correct Answer: A

---

#### QUESTION 4

On the Ethernet Routing Switch (ERS) 8800, the Virtual Routing Forwarding (VRF)-Lite feature supports multicast virtualization. Which statements about multicast virtualization are true? (Choose two)

- A. Multicast virtualization is fully supported in high availability mode and there is no interruption to traffic in the event of the failure of a CPU.
- B. Multicast virtualization requires version 7.1 or later.
- C. To facilitate multicast route redistribution between VRFs, an external unicast edge router is required.
- D. Many IGMP and PIM commands that you use on the Global Router also apply to VRFs that create.

Correct Answer: AD

---

#### QUESTION 5

What is the front panel port configuration for the Ethernet Routing Switch (ERS) 2550T-PWR?

- A. 48 10/100 BaseT ports (PoE on 48 ports)Two combo 10/100/1000BaseT or SFP port
- B. 48 10/100BaseT ports (PoE on 24 ports)two combo 10/100/1000BaseT or SFP port
- C. 50 10/100BaseT ports (PoE on 25 ports)two combo 10/100/1000BaseT or SFP port
- D. 50 10/100BaseT ports (PoE on 50 ports)two combo 10/100/1000BaseT or SFP port

Correct Answer: B

[Latest 3605 Dumps](#)

[3605 PDF Dumps](#)

[3605 Braindumps](#)