



3V0-42.20^{Q&As}

Advanced Design VMware NSX-T Data Center

Pass VMware 3V0-42.20 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/3v0-42-20.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by VMware
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





QUESTION 1

Which two resources can be used by an NSX architect during the Assessment Phase? (Choose two.)

- A. vRealize Network Insight
- B. VMware Validated Design
- C. VMware customer references
- D. key stakeholder interviews
- E. application licensing

Correct Answer: AE

QUESTION 2

An architect is helping an organization with the Physical Design of an NSX-T Data Center solution.

This information was gathered during the Assessment Phase:

There is a critical application used by the Finance Team.

The critical application has an availability and recoverability SLA of 99.999%.

The critical application is sensitive to network changes.

Which two selections should an architect include in their design? (Choose two.)

- A. Configure Tier-0 gateway for eBGP and ECMP.
- B. Configure Tier-1 gateway for eBGP and ECMP.
- C. Enable BFD on Tier-0 gateway.
- D. Install and configure hosts with 100Gbps physical NICs.
- E. Configure multiple static routes on Tier-1 gateway.

Correct Answer: BD

QUESTION 3

A Solution Architect will be deploying an Ethernet Virtual Private Network (EVPN) in their NSX-T Data Center environment.

What two selections must be prepared for the EVPN deployment? (Choose two.)

- A. deployed Tier-0 gateway
- B. deployed Load Balancer
- C. deployed Tier-1 gateway
- D. remote gateway with support for IGP and VLAN priority
- E. remote gateway with support for MP-BGP and VXLAN

Correct Answer: BE

Reference: https://docs.vmware.com/en/VMware-NSX-T-Data-Center/3.0/nsxt_30_admin.pdf

QUESTION 4

Which two benefits can be achieved using in-band management of an NSX Bare Metal Edge Node? (Choose two.)

- A. Reduces storage requirements.
- B. Reduces cost.
- C. Preserves packet locality.
- D. Reduces egress data.
- E. Preserves switchports.

Correct Answer: BD

QUESTION 5

An architect is helping an organization with the Logical Design of an NSX-T Data Center solution.

This information was gathered during the Assessment Phase:

Maximum performance and availability is required between the physical and virtual network.

Load Balancing service is required for back-end web servers.

NAT is required.

Which selection should the architect include in their design? (Choose the best answer.)

- A. Deploy a Tier-1 gateway and connect it to an Active/Active Tier-0 gateway with ECMP configured.
- B. Deploy an Active/Active Tier-0 gateway and configure ECMP.
- C. Deploy an Active/Standby Tier-0 gateway and configure ECMP.
- D. Create two separate VLANs to connect the Tier-0 gateway upstream traffic and configure ECMP.

Correct Answer: C



VCE & PDF

PassApply.com

<https://www.passapply.com/3v0-42-20.html>

2024 Latest passapply 3V0-42.20 PDF and VCE dumps Download

[Latest 3V0-42.20 Dumps](#)

[3V0-42.20 Study Guide](#)

[3V0-42.20 Exam Questions](#)