



4A0-104^{Q&As}

Alcatel-Lucent Services Architecture





Pass Alcatel-Lucent 4A0-104 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/4a0-104.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Alcatel-Lucent Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

Which of the following statements is FALSE regarding SAPs?

- A. VPWS: SAPs can be defined on Ethernet, POS, Sonet/SDH, or TDM channels.
- B. VPWS: Two SAPs are defined for a service that originates and terminates on the same Nokia 7750 SR
- C. VPLS: More than two SAPs can be defined in a service.
- D. VPWS: SAPs are associated with an IP interface.

Correct Answer: D

QUESTION 2

Which of the following about the lsp-ping command on the Nokia 7750 SR is FALSE?

- A. An echo request is sent based on the LSP's label stack.
- B. Echo reply packets may not take the same path as the LSP.
- C. The IP destination address is used to initiate echo requests.
- D. The test fails if the LSP is not operationally up.

Correct Answer: C

QUESTION 3

By default, what does a Nokia 7750 SR do to support VPLS services for different customers?

- A. Dedicates a separate port for each customer.
- B. Performs ARP look-ups for each service.
- C. Maintains a different IP routing table for each service.
- D. Maintains a different MAC Forwarding Database for each service.

Correct Answer: D

QUESTION 4

VPWS allows carriers to offer services such as point-to-point frame-relay, ATM, and Ethernet on a single platform without the need for multiple overlay networks.

- A. TRUE



B. FALSE

Correct Answer: A

QUESTION 5

Which of the following about IES is FALSE?

- A. An IES provides a Layer 3 interface to a customer.
- B. A virtual routing/forwarding table is created per IES service.
- C. An IES supports QoS.
- D. An IES interface's IP address, if bound to a port, will appear in the routing table.

Correct Answer: B

[4A0-104 VCE Dumps](#)

[4A0-104 Exam Questions](#)

[4A0-104 Braindumps](#)