



4A0-108^{Q&As}

Alcatel-Lucent Multicast Protocols

Pass Alcatel-Lucent 4A0-108 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/4A0-108.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Alcatel-Lucent Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

Which of the following about MLD snooping is FALSE?

- A. MLD snooping enables switches to forward multicast data to specific hosts interested in the group.
- B. MLD snooping can co-exist with IGMP snooping in the same VPLS service.
- C. Once MLD snooping is enabled, the switch can snoop both MLDv1 and MLDv2 messages.
- D. MLD snooping snoops MLD report and done messages, but not query messages.

Correct Answer: D

QUESTION 2

What is the destination address of the MLDv2 general query?

- A. FF02::1
- B. FF02::2
- C. FF02::16
- D. The multicast group address of the multicast data that the router is receiving

Correct Answer: A

QUESTION 3

Which of the following about the I-PMSI is TRUE?

- A. The I-PMSI enables a PE to transmit packets to a subset of PEs in the MVPN.
- B. An I-PMSI cannot be instantiated by MPLS P2MP P-tunnels.
- C. The I-PMSI is created and signaled by PIM or BGP Auto Discovery.
- D. An I-PMSI can be reused in multiple MVPNs.

Correct Answer: C

QUESTION 4

How often will a router issue IGMP Host Membership Reports for group 224.0.0.2?

- A. Never
- B. 30 seconds



- C. 60 seconds
- D. 120 seconds
- E. 260 seconds
- F. A router will never join this group

Correct Answer: A

QUESTION 5

Why should the anycast RP address be a non-system address of a router?

- A. Alcatel-Lucent 7750 SR configuration does not permit using the system address for an anycast RP address.
- B. The system address of a router must be a unique address within the domain, while the anycast address is configured on multiple routers within the domain.
- C. PIM will not be able to establish its signaling sessions if the anycast address uses the system address.
- D. Best practice is to use the system address as the anycast address for PIM.

Correct Answer: B

[4A0-108 Practice Test](#)

[4A0-108 Study Guide](#)

[4A0-108 Exam Questions](#)



To Read the [Whole Q&As](#), please purchase the [Complete Version](#) from [Our website](#).

Try our product !

100% Guaranteed Success
100% Money Back Guarantee
365 Days Free Update
Instant Download After Purchase
24x7 Customer Support
Average 99.9% Success Rate
More than 800,000 Satisfied Customers Worldwide
Multi-Platform capabilities - [Windows](#), [Mac](#), [Android](#), [iPhone](#), [iPod](#), [iPad](#), [Kindle](#)

We provide exam PDF and VCE of Cisco, Microsoft, IBM, CompTIA, Oracle and other IT Certifications.
You can view Vendor list of All Certification Exams offered:

<https://www.passapply.com/allproducts>

Need Help

Please provide as much detail as possible so we can best assist you.
To update a previously submitted ticket:



 <p>One Year Free Update Free update is available within One Year after your purchase. After One Year, you will get 50% discounts for updating. And we are proud to boast a 24/7 efficient Customer Support system via Email.</p>	 <p>Money Back Guarantee To ensure that you are spending on quality products, we provide 100% money back guarantee for 30 days from the date of purchase.</p>	 <p>Security & Privacy We respect customer privacy. We use McAfee's security service to provide you with utmost security for your personal information & peace of mind.</p>
---	---	--

Any charges made through this site will appear as Global Simulators Limited.
All trademarks are the property of their respective owners.
Copyright © passapply, All Rights Reserved.