



4A0-M10^{Q&As}

Nokia 5G Packet Core Architecture

Pass Nokia 4A0-M10 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/4a0-m10.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Nokia
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

Which Nokia product is used for the AMF in 5GS?

- A. Cloud Mobility Manager
- B. Cloud Mobile Gateway
- C. Network Resource Discovery
- D. Smart Plan Suite

Correct Answer: A

Reference: <https://www.nokia.com/networks/products/cloud-mobility-manager/>

QUESTION 2

Which of the following statements about the protection of service-based interfaces (SBIs) is FALSE?

- A. The transport layer security (TLS) performs certification-based authentication, providing connection security between network functions within a PLMN.
- B. The OAuth 2.0 framework is used to secure the communication between network functions within a PLMN at the network layer.
- C. The network domain security/Internet protocol (NDS/IP) provides confidentiality and data integrity between network functions within a PLMN.
- D. The security edge protection proxy (SEPP) handles the security of inter-domain SBIs and protects the interaction between network functions in different PLMNs.

Correct Answer: D

Reference: <https://www.broadforward.com/security-edge-protection-proxy/>

QUESTION 3

Which of the following statements about the downlink user plane data flow in Option 3X is FALSE?

- A. Data packets of bearers that do not use dual connectivity are sent from EPC to UE through eNB.
- B. When NR coverage is good, data packets of bearers that use dual connectivity are sent from EPC to UE using secondary cell group bearers.
- C. When NR coverage degrades, the gNB decides when to use split bearers and send some of the packets received from the core through eNB.
- D. When NR coverage is poor, data packets of bearers that use dual connectivity are sent to the UE through eNB.

Correct Answer: D



QUESTION 4

Which of the following best describes the Secondary Node Addition procedure?

- A. Used to transfer bearer contexts from the master eNB to the secondary gNB.
- B. Used to establish a UE context at the gNB for a UE that supports option 3X.
- C. Used to establish connectivity from the gNB to the EPC.
- D. Used to establish an X2 connection between the eNB and gNB.

Correct Answer: D

QUESTION 5

A UE has a PDU session established using slice 1. The operator removes slice 1 from the UE subscription data stored in UDM. Which of the following actions is NOT performed as a result?

- A. UDM notifies the serving AMF about the UE subscription data modification.
- B. AMF initiates the UE configuration update procedure.
- C. AMF requests the UE to release the established PDU session.
- D. UE updates its slicing information with the data received from AMF.

Correct Answer: B

[4A0-M10 PDF Dumps](#)

[4A0-M10 Study Guide](#)

[4A0-M10 Braindumps](#)