



# 4A0-M10<sup>Q&As</sup>

Nokia 5G Packet Core Architecture

**Pass Nokia 4A0-M10 Exam with 100% Guarantee**

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/4a0-m10.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Nokia  
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





#### QUESTION 1

Which of the following statements about non-access stratum mobility management (NAS-MM) protocol is TRUE?

- A. It runs between the UE and the SMF.
- B. It is used to control user plane resources between the UE and a data network.
- C. It provides common procedures such as authentication, identification, and UE configuration update.
- D. NAS-MM messages are relayed transparently by the AMF.

Correct Answer: C

---

#### QUESTION 2

Which of the following statements about 5GS PDU sessions is FALSE?

- A. A PDU session allows for the exchange of PDUs between UE and a data network.
- B. A PDU session contains one single dedicated radio bearer and one or more N3 GTP-U tunnels.
- C. A PDU session has one default QoS flow and can have multiple non-default QoS flows.
- D. A PDU session has one or more UPFs acting as PDU session anchors.

Correct Answer: B

---

#### QUESTION 3

Which of the following statements regarding cloud RAN architecture is FALSE?

- A. The gNB is split into three functional modules: a radio unit (RU), a distributed unit (DU), and a centralized unit (CU).
- B. DU performs the non-real time processing of layer 2.
- C. The fronthaul segment connects RU to DU and the midhaul segment connects DU to CU.
- D. CU can be deployed in the cloud as a VNF.

Correct Answer: D

Reference: <https://www.5gtechnologyworld.com/open-ran-functional-splits-explained/>

---

#### QUESTION 4



Which of the following actions is NOT performed when handling an uplink data packet?

- A. UE maps the uplink data packet to a QoS Flow based on QoS rules received from SMF.
- B. UE maps the QoS Flow identifier to a data radio bearer based on QFI-to-DRB mapping received from NG-RAN.
- C. NG-RAN marks the data packet with the proper DSCP value.
- D. NG-RAN removes the QoS Flow identifier from the packet header and forwards the packet over the proper N3 GTP-U tunnel.

Correct Answer: A

---

#### QUESTION 5

In which of the following scenarios is the Service Request procedure performed?

- A. A deregistered UE needs to register with the network.
- B. A registered UE receives a paging request from the network.
- C. A registered UE needs to establish a new PDU session.
- D. A deregistered UE needs to connect to the network using non-3GPP access.

Correct Answer: C

[4A0-M10 PDF Dumps](#)

[4A0-M10 VCE Dumps](#)

[4A0-M10 Study Guide](#)