



# 4A0-M10<sup>Q&As</sup>

Nokia 5G Packet Core Architecture

**Pass Nokia 4A0-M10 Exam with 100% Guarantee**

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/4a0-m10.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Nokia  
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





### QUESTION 1

Which of the following actions related to slicing is NOT performed during UE initial registration procedure?

- A. An AMF that supports the requested NSSAI is selected to serve the UE.
- B. AMF receives an AMF set from NSSF.
- C. AMF receives a list of SMFs which support the requested NSSAI from NRF.
- D. UE receives the allowed NSSAI from AMF.

Correct Answer: B

---

### QUESTION 2

Which of the following statements about the protection of service-based interfaces (SBIs) is FALSE?

- A. The transport layer security (TLS) performs certification-based authentication, providing connection security between network functions within a PLMN.
- B. The OAuth 2.0 framework is used to secure the communication between network functions within a PLMN at the network layer.
- C. The network domain security/Internet protocol (NDS/IP) provides confidentiality and data integrity between network functions within a PLMN.
- D. The security edge protection proxy (SEPP) handles the security of inter-domain SBIs and protects the interaction between network functions in different PLMNs.

Correct Answer: D

Reference: <https://www.broadforward.com/security-edge-protection-proxy/>

---

### QUESTION 3

Which of the following statements about non-access stratum mobility management (NAS-MM) protocol is TRUE?

- A. It runs between the UE and the SMF.
- B. It is used to control user plane resources between the UE and a data network.
- C. It provides common procedures such as authentication, identification, and UE configuration update.
- D. NAS-MM messages are relayed transparently by the AMF.

Correct Answer: C



#### QUESTION 4

Which 5GS network function allows UE connectivity to 5GC through non-3GPP access networks?

- A. SEPP
- B. N3IWF
- C. NWDAF
- D. NEF

Correct Answer: C

---

#### QUESTION 5

When an idle UE moves from EPS to 5GS, which procedure is performed?

- A. Registration
- B. Tracking Area Update
- C. Initial Attach
- D. Service Request

Correct Answer: C

Reference: <https://itectec.com/spec/5-17-interworking-and-migration/>

[4A0-M10 PDF Dumps](#)

[4A0-M10 Study Guide](#)

[4A0-M10 Braindumps](#)