



# 4A0-N01<sup>Q&As</sup>

Nuage Networks Virtualized Cloud Services (VCS) Fundamentals

## Pass Nokia 4A0-N01 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/4a0-n01.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Nokia  
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





### QUESTION 1

What is the difference between host vPort and bridge vPort?

- A. A host vPort is provisioned on VRS-G, while a bridge vPort is provisioned on VSG.
- B. A host vPort is provisioned for VLAN traffic, while a bridge vPort is for VxLAN traffic.
- C. A host vPort only supports one VLAN, while a bridge vPort can be configured with multiple VLANs.
- D. A host vPort requires static MAC address configuration, while a bridge vPort learns MAC addresses dynamically.

Correct Answer: A

Bridge vPort hosted in Nuage VSG/VSA Gateways Software, VRS and VRS-G hosted vPort

Reference: <https://matscloud.blogspot.com/2017/06/nuage-networks-vsp-deep-dive.html>

---

### QUESTION 2

Which of the following interfaces is not supported on VSC?

- A. API interface
- B. BGP interface
- C. Openflow interface
- D. XMPP interface

Correct Answer: A

Reference:

<https://www.nuagenetworks.net/wp-content/uploads/2020/06/>

Nuage\_Networks\_Service\_Chaining\_Technical\_Description\_Document\_EN-compressed.pdf

---

### QUESTION 3

For a packet transmitted using VXLAN encapsulation, where is the VXLAN header within the packet?

- A. It is part of the Layer 2 Ethernet header, just like VLAN.
- B. It is added between the Layer 2 header and the Layer 3 IP header.
- C. It is added between the Layer 3 IP header and the TCP/UDP transport layer header.
- D. It is added between the UDP header and the payload.

Correct Answer: C



Reference: <https://openct.net/wp-content/uploads/OpenCT-BaaT-Technical-Documentation-2020.pdf>

---

#### QUESTION 4

What occurrence is NOT a problem facing a traditional data center network?

- A. High packet loss due to the use of the 3-tier hierarchy.
- B. Sub-optimal traffic flow.
- C. About half of the bandwidth is not used due to links being disabled by STP.
- D. High latency for some applications.

Correct Answer: B

Reference: <https://nsl.cs.sfu.ca/teaching/13/880/surveyVirtualization.pdf>

---

#### QUESTION 5

What function is NOT supported on the Nuage 7850 VSG?

- A. Hardware VXLAN/VLAN gateway
- B. Cloud orchestration
- C. Top of Rack switch/Leaf router
- D. VSC functionality

Correct Answer: B

[Latest 4A0-N01 Dumps](#)

[4A0-N01 VCE Dumps](#)

[4A0-N01 Practice Test](#)