



500-220^{Q&As}

Cisco Meraki Solutions Specialist

Pass Cisco 500-220 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/500-220.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

DRAG DROP

Drag and drop the settings from the left into the boxes on the right to indicate if the setting will be cloned or not cloned using the Cisco Meraki MS switch cloning feature.

Select and Place:

switch management IP	Cloned
switch name	
port name	
interface type	Not Cloned
STP bridge property	

Correct Answer:



Cloned

- switch management IP
- interface type
- STP bridge property

Not Cloned

- switch name
- port name

QUESTION 2

When an SSID is configured with Sign-On Splash page enabled, which two settings must be configured for unauthenticated clients to have full network access and not be allow listed? (Choose two.)

- A. Controller disconnection behavior
- B. Captive Portal strength
- C. Simultaneous logins
- D. Firewall and traffic shaping
- E. RADIUS for splash page settings

Correct Answer: AB

Reference: https://documentation.meraki.com/MR/Access_Control

QUESTION 3

Outbound rules	#	Policy	Protocol	Source	Src port	Destination	Dst port	Comment	Logging	Hits	Actions
		Allow	Any	Any	Any	Any	Any	Default rule	Enabled	2	
Add a rule											

Refer to the exhibit. Which outcome occurs when logging is set to Enabled?



- A. Outbound flows are sent to a configured syslog server if a syslog sender is configured for flows.
- B. The hits counter within this section is now enabled.
- C. This firewall rule is now enabled.
- D. Inbound flows are sent to a configured syslog server if a syslog server configured for flows.

Correct Answer: A

QUESTION 4

Where should a network admin navigate to investigate wireless mesh information between Meraki APs?

- A. Wireless > Monitor > Access Points > AP > RF
- B. Wireless > Configure > Radio Settings
- C. Wireless > Monitor > Wireless Health
- D. Wireless > Monitor > RF Spectrum

Correct Answer: A

QUESTION 5



Uplink selection

Global preferences

Primary uplink

WAN 1

Load balancing

- Enabled
Traffic will be spread across both uplinks in the proportions specified above. Management traffic to the Meraki cloud will use the primary uplink.
- Disabled
All Internet traffic will use the primary uplink unless overridden by an uplink preference or if the primary uplink fails.

Active-Active AutoVPN

- Enabled
Create VPN tunnels over all of the available uplinks (primary and secondary).
- Disabled
Do not create VPN tunnels over the secondary uplink unless the primary uplink fails.

Flow preferences

Internet traffic

There are no uplink preferences for Internet traffic configured on this network.
[Add a preference](#)

SD-WAN policies

VPN traffic

There are no uplink preferences for VPN traffic configured on this network.
[Add a preference](#)

Custom performance classes

Name	Maximum latency (ms)	Maximum jitter (ms)	Maximum loss (%)	Actions
VoIP	150	(none)	(none)	×

[Create a new custom performance class](#)

Refer to the exhibit. What does the MX Security Appliance send to determine whether VPN traffic exceeds the configured latency threshold in the VoIP custom performance class?

- A. 1000-byte TCP probes every second, through VPN tunnels that are established over the primary WAN link.
- B. 100-byte UDP probes every second, through VPN tunnels that are established over every WAN link.
- C. 100-byte UDP probes every second, through VPN tunnels that are established over the primary WAN link.
- D. 1000-byte TCP probes every second, through VPN tunnels that are established over every WAN link.

Correct Answer: C

[Latest 500-220 Dumps](#)

[500-220 VCE Dumps](#)

[500-220 Braindumps](#)