500-230^{Q&As}

500-230^{Q&As}

Cisco Service Provider Routing Field Engineer

Pass Cisco 500-230 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.passapply.com/500-230.html

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco Official Exam Center

Instant Download After Purchase

100% Money Back Guarantee

365 Days Free Update

800,000+ Satisfied Customers

QUESTION 1

How are labels exchanged between the AS\\'es in an Option B Layer-3 VPN solution?

A. Via an eBGP multihop connection between the Ingress PE\\'s in each AS.

B. Via an eBGP multihop connection between a Route-Reflector in each AS.

C. There are no labels exchanged between the two AS\\'es.

D. Via an eBGP connection between the directly connected ASBR\\'s, one in each AS.

Correct Answer: D

QUESTION 2

What command is used to manually generate a core dump to aid in troubleshooting a process?

A. context

B. dumpcore

C. exception

D. follow

Correct Answer: C

QUESTION 3

Which command is used to redistribute BGP into EIGRP for a Layer 3 VPN customer?

A. router(config-eigrp-af)# redistribute bgp 65001

B. router(config-eigrp-vrf-af)# redistribute bgp 65001

C. rouur(config-eigrp-vrf)# redistribute bgp 65001

D. router(config-eigrp)# redistribute bgp 65001

Correct Answer: B

QUESTION 4

How many times are Layer 3 lookups performed on a packet transiting a CRS or ASR9k router?

A. Three times: in the ingress linecard, the fabric, and the egress linecard

B. Once: in the active RP/RSP

C. Once: in the ingress linecard

D. Twice: in the ingress linecard and again in the egress linecard

Correct Answer: A

QUESTION 5

Which statements are true regarding L3VPN configurations?

A. Prior to configuring a vrf within MP-BGP, the router has to have instantiated the VPNv4 or VPNv6 address-family.

B. On a single PE router, the Route Distinguisher and the Route Targets must be the same.

C. Prior to configuring a neighbor in the VPNv4 address-family, it must already be configured for IPv4Unicast.

D. The import and export Route Targets must be the same on a PE.

Correct Answer: C

[500-230 PDF Dumps](https://www.passapply.com/500-230.html)   [500-230 VCE Dumps](https://www.passapply.com/500-230.html)   [500-230 Study Guide](https://www.passapply.com/500-230.html)