



# 500-440<sup>Q&As</sup>

Designing Cisco Unified Contact Center Enterprise (UCCED)

## Pass Cisco 500-440 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/500-440.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco  
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





### QUESTION 1

In Cisco Finesse 10.0(x), a supervisor has the capability to Monitor, Intercept, and Barge an agent call. Under which condition can a supervisor successfully intercept the call?

- A. after a supervisor has started monitoring a call
- B. after a supervisor has barged into a call
- C. after a supervisor has selected a talking agent for monitoring
- D. after a supervisor has conferenced into a call
- E. after a supervisor has transferred the call

Correct Answer: B

---

### QUESTION 2

Which two options are the maximum number of concurrent reports supported with the Packaged CCE Data Server Release 10.5? (Choose two.)

- A. 100 concurrent Real-time reports
- B. 400 concurrent Real-time reports
- C. 800 concurrent Real-time reports
- D. 50 concurrent Historical reports
- E. 100 concurrent Historical reports
- F. 200 concurrent Historical reports

Correct Answer: BF

---

### QUESTION 3

Which two statements about Cisco Unified Customer Voice Portal Whisper Announcements are true? (Choose two.)

- A. In Whisper Announcements, wave files must match Cisco Unified CVP encoding and format requirements (G.711, CCITT A-Law 8 kHz, 8 bit, mono).
- B. The maximum play time for a Whisper Announcement is subject to a timeout (default 45 sec).
- C. A maximum of two Whisper Announcements can play for each call.
- D. In Whisper Announcements, wave (.wav) is the only supported file type.
- E. While a Whisper Announcement is playing, the agent can put the call on hold.



Correct Answer: AD

---

#### QUESTION 4

When using microapps, which core components are required for calls that originate from Cisco Unified Communications Manager to Cisco Unified CVP using Comprehensive mode?

- A. CUCM: CTI Route Point and SIP Trunk, ICM: CVP Type 2 VRU and Network VRU labels, VXML Gateway
- B. CUCM: CTI Route Port, SIP Trunk, ICM: CVP Type 2 VRU, CUBE, VXML Gateway
- C. SIP Trunk, ICM: CVP Type 7 VRU and Network VRU labels, VXML Gateway
- D. CUCM: CTI Route Point and SIP Trunk, ICM: CVP Type 10 VRU and Network VRU labels, VXML Gateway

Correct Answer: D

---

#### QUESTION 5

Which Cisco Unified Border Element configuration is correct when deployed with Cisco UCCE Unified CVP?

- A. You must dedicate a voice gateway for VXML browser sessions.
- B. You must configure Cisco Unified Border Element as media pass flow-around mode.
- C. You must configure Cisco Unified Border Element as media pass flow-through mode.
- D. You must use box-to-box Cisco Unified Border Element redundancy.

Correct Answer: C

[Latest 500-440 Dumps](#)

[500-440 PDF Dumps](#)

[500-440 Exam Questions](#)