



500-450^{Q&As}

Implementing and Supporting Cisco Unified Contact Center Enterprise (UCCEIS)

Pass Cisco 500-450 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/500-450.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco
Official Exam Center

- ⚙ **Instant Download** After Purchase
- ⚙ **100% Money Back** Guarantee
- ⚙ **365 Days** Free Update
- ⚙ **800,000+** Satisfied Customers





QUESTION 1

When configuring the Cisco CVP Courtesy Callback feature in the ingress and VXML gateway, which configuration is needed to ensure that SIP is set up to forwards SIP INFO messaging.

- A. signaling forward unconditional
- B. signaling forward conditional
- C. signaling forward conditional sip info
- D. signaling forward unconditional sip info
- E. signaling sip forward unconditional

Correct Answer: A

QUESTION 2

Which statement about when you deploy Cisco Unified CCE on Cisco UCS C-Series Tested Reference Configuration Servers is true?

- A. You check/calculate if you have enough IOPS as described on Cisco Unified CCE docwiki VMs storage requirements.
- B. You do not need to check/calculate if you have enough IOPS as described on Cisco Unified CCE docwiki VMs storage requirements.
- C. You can add more disks to the Cisco UCS C-Series TRCs to meet IOPS requirements.
- D. You cannot add more disks, but you can connect the Cisco UCS C-Series TRC to the SAN in the network to meet IOPS requirements.

Correct Answer: B

QUESTION 3

Which option describes how many reason codes you can assign across all teams using Cisco Finesse?

- A. 50 sign-out reason codes and 50 not ready reason codes for a total of 100.
- B. A total of 100 sign-out reason codes and not ready reason codes.
- C. There is no limit. You can assign as many reason codes as you like.
- D. 100 sign-out reason codes and 100 not ready reason codes for a total of 200.



Correct Answer: D

QUESTION 4

Which option best describes the issue with a call failing at the Send to VRU node in a comprehensive Cisco CVP deployment?

- A. Call type is not mapped to the ICM script.
- B. VRU label in the CVP dial plan does not match the dial peer on the VXML gateway.
- C. CVP server is running on temporary licenses.
- D. VXML application is not deployed to the CVP servers.

Correct Answer: B

QUESTION 5

A new gateway was added to the Cisco CVP in a comprehensive deployment and calls are failing with error "403 forbidden".

What is the possible cause?

- A. Gateway cache requires a reset.
- B. Toll Fraud security is not configured correctly.
- C. Gateway authentication has not been configured.
- D. Gateway IP has been blacklisted.

Correct Answer: B

[500-450 PDF Dumps](#)

[500-450 Study Guide](#)

[500-450 Braindumps](#)