500-470^{Q&As}

Cisco Enterprise Networks SDA, SDWAN and ISE Exam for System Engineers

Pass Cisco 500-470 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.passapply.com/500-470.html

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco Official Exam Center

⚙ **Instant Download** After Purchase

⚙ **100% Money Back** Guarantee

⚙ **365 Days** Free Update

⚙ **800,000+** Satisfied Customers

QUESTION 1

Which are three key features within the Cisco ISE that mainly compete with the other RADIUS and NAC products? (Choose three.)

A. BYOD provides auto configuration of endpoints.

B. Deep packet inspection upon authorization of endpoints.

C. Guest access and guest lifecycle management functionality.

D. Software based firewall capabilities for selected devices and endpoints.

E. Ability to authenticate and authorize users and endpoints.

Correct Answer: ACE

QUESTION 2

Which three wireless product families are supported in the current DNA-C 1.1 release? (Choose three.)

A. AP 1260

B. WLC 8540

C. WLC 5508

D. AP 3800

E. WLC 3504

Correct Answer: BDE

QUESTION 3

What is a challenge of having an SD-Access Centralized design where a single fabric encompasses the main site and all branch sites across the WAN?

A. End to End Routing is not supported

B. SSIDs would be the same across all sites

C. DNA Center does not support it

D. Since the traffic is encapsulated. SD-WAN features can\\'t be used to optimize/route traffic.

Correct Answer: A

QUESTION 4

What is an example of Correlated Insights for SDA and Switching?

A. Excessive Onboarding Time

B. Roaming Pattern Analysis

C. Control Plane Reachability

D. AP License Utilization

Correct Answer: C

Reference:http://www.tyrc.edu.tw/images/2/29/107051006.pdf page 72

QUESTION 5

Device Sensor provides which two types of information to ISE? (Choose two.)

A. DHCP

B. Encrypted traffic

C. User/Device Name

D. CDP

E. NetFlow

Correct Answer: AD

Reference:https://www.cisco.com/c/en/us/support/docs/security/identity-services-engine/200292Configure-Device-Sensor-for-ISE-Profilin.html?referring_site=REandpos=1andpage=https://www.cisco.com/c/en/us/td/docs/switches/lan/catalyst3750/software/release/15-0_1_se/device_sensor/guide/ sensor_guide.html