



500-901^{Q&As}

Cisco Data Center Unified Computing Infrastructure Design

Pass Cisco 500-901 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/500-901.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

What is a Universally Unique Identifier in the context of Cisco Unified Computing System?

- A. A unique identifier used to identify an object or entity on the internet.
- B. A unique identifier used in server profiles enabling server mobility.
- C. A unique identifier used in application profiles enabling server mobility.
- D. A unique identifier used in service profiles enabling server mobility.

Correct Answer: D

QUESTION 2

Cisco recommended to help customer's provision physical, virtual, and multivendor data center infrastructure environments from a single pane?

- A. Cisco UCS Director
- B. Cisco UCS Performance Manager
- C. Cisco UCS Manager
- D. Cisco UCS Central

Correct Answer: C

QUESTION 3

An application is running in a data center as a set of virtual machines running on a single physical host. The host is using an NPIV enabled HBA.

What capability does this offer?

- A. Only the physical host can logically connect to the SAN fabric, thus enhancing security.
- B. The number of FIOGIs is kept at a reasonable level, and therefore cannot saturate the SAN fabric.
- C. Inter VSAN traffic can be switched directly by the HBA.
- D. Each VM initiator can be managed independently, since it will generate its own FLOGI, and have its own pWWN.

Correct Answer: D

QUESTION 4

When can you use UCS Director to provision Service Profile template?



- A. For initial Service Profile template
- B. Always
- C. Never
- D. Only for updating Service Profile template

Correct Answer: A

QUESTION 5

In the context of Cisco's unified Computing System, which three Cisco best practices are recommended when creating WWN pools? (Choose three.)

- A. All WWN must use "20" for the first octet
- B. Define a standard convention for WWNs agreed upon by all stakeholders for address blocks
- C. Select the default values presented by UCS Central
- D. Use Cisco's OUI (00:25:B5) for the 3rd to 5th octets in WWN
- E. Use the same hex value for 1st and 2nd octets in WWNN and WWPNN
- F. Engage the security team to request WWNs

Correct Answer: ADE

[500-901 Practice Test](#)

[500-901 Study Guide](#)

[500-901 Braindumps](#)