



500-920^{Q&As}

Cisco Data Center Unified Computing Infrastructure Troubleshooting
(DCITUC)

Pass Cisco 500-920 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/500-920.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco
Official Exam Center

- ⚙ **Instant Download** After Purchase
- ⚙ **100% Money Back** Guarantee
- ⚙ **365 Days** Free Update
- ⚙ **800,000+** Satisfied Customers





QUESTION 1

A new UCS dual fabric cluster is being configured with a single chassis. The administrator notices that the cluster is not in High Availability (HA) mode. What is the possible cause?

- A. No uplinks are active into the data center.
- B. The links to the chassis are not enabled
- C. The HA plugin has not been installed in UCS Manager
- D. The UCS-FI-HA license has not been activated in UCS Manager

Correct Answer: C

QUESTION 2

Which two interfaces allow access to Cisco UCS Manager? (Choose two)

- A. Cisco KVM
- B. Cisco UCS Manager XML API
- C. Cisco IMC
- D. Cisco UCS Manager GUI

Correct Answer: BD

QUESTION 3

Which two components are required when the integration of Cisco UCS C-series servers within a Cisco UCS Manager Direct Connect mode? (Choose two)

- A. Compatible Cisco Nexus Fabric Extenders
- B. Cisco Management Controller
- C. Compatible UCS VIC adapter installed via the server's PCIe or MLOM slot
- D. Compatible UCS 6200 or 6300 Fabric Interconnects
- E. Compatible Cisco UCS Manager version

Correct Answer: CD

QUESTION 4

When troubleshooting a LAN connectivity issue, you notice a failed uplink from the Cisco UCS Fabric Interconnects to



the upstream LAN switch. What two could be causing the issue? (Choose two)

- A. Misconfigured VLAN on the failed uplink
- B. Misconfigured QoS parameters on the failed uplink
- C. A port channel mismatch between the Fabric Interconnects and the upstream LAN switch
- D. A SFP Type mismatch between the Fabric Interconnects and the upstream LAN switch
- E. A port speed configuration mismatch between the Fabric Interconnects and the upstream LAN switch

Correct Answer: BC

QUESTION 5

Which statement regarding the UCS C-series connectivity modes best describes connectivity options in a UCS Manager integrated environment?

- A. UCS C-series servers must be connected to Fabric Interconnects using Fabric Extenders (FEX)
- B. UCS C-series servers may be connected to multiple UCS Manager domains at the same time
- C. All UCS C-series servers in a single UCS Manager domain must share the same connectivity model
- D. UCS C-series servers may be connected with or without the use of Fabric Extenders (FEX) in environments running UCS Manager Software Release 2.2 or later

Correct Answer: D

[Latest 500-920 Dumps](#)

[500-920 PDF Dumps](#)

[500-920 Braindumps](#)