



# 500-920<sup>Q&As</sup>

Cisco Data Center Unified Computing Infrastructure Troubleshooting  
(DCITUC)

## Pass Cisco 500-920 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/500-920.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco  
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





### QUESTION 1

Which two statements describes connecting the IO Modules in the UCS chassis to the Fabric interconnects? (Choose two )

- A. Connect FI-A to the IOM B of each chassis
- B. Connect FI-B to IOM A and IOM B in each chassis
- C. Connect FI-A to the IOM A of each chassis
- D. Connect FI-A to IOM A and IOM B in each chassis
- E. Connect FI-B to the IOM A of each chassis
- F. Connect FI-B to the IOM B of each chassis

Correct Answer: ACF

---

### QUESTION 2

When booting up a Cisco UCS Server you want to see boot time diagnostic messages of the POST, what action is required for you to do so?

- A. Enable Quiet Boot on the Server\\'s BIOS
- B. Restart the Server
- C. Disable Fast Boot on the Server\\'s BIOS
- D. Enable Quiet Boot on the Server\\'s Service Profile
- E. Disable Fast Boot on the Server\\'s Service Profile

Correct Answer: D

---

### QUESTION 3

Which two interfaces allow access to Cisco UCS Manager? (Choose two )

- A. Cisco KVM
- B. Cisco UCS Manager XML API
- C. Cisco IMC
- D. Cisco UCS Manager GUI

Correct Answer: BD

---



#### QUESTION 4

What are three possible causes of service profile association failure due to iSCSI configuration issue? (Choose three )

- A. Wrong WWNN
- B. iSCSI Target out of configured range of services
- C. Inappropriate network configuration
- D. Improperly assigned iSCSI Class of Service
- E. Misconfigured iSCSI parameters
- F. Misconfigured LUN. LUN masking

Correct Answer: BCE

---

#### QUESTION 5

When configuring UCS SAN Connectivity to a 3rd Party FibreChannel Storage Array that is connecting directly to the UCS Fabric Interconnects, which option is Cisco recommended\?

- A. Connect the Storage Array to a RC Storage Port and Enable NPV Mode on the UCS Fabric Interconnects
- B. Connect the Storage Array to an Appliance Port and Enable NPV Mode on the UCS Fabric Interconnects
- C. Direct connectivity between UCS Fabric Interconnects and FibreChannel Storage Arrays is not supported
- D. Connect the Storage Array to a FC Storage Port and Enable Switching Mode on the UCS Fabric Interconnects
- E. Connect the Storage Array to an Appliance Port and Enable Switching Mode on the UCS Fabric Interconnects

Correct Answer: D

[Latest 500-920 Dumps](#)

[500-920 PDF Dumps](#)

[500-920 VCE Dumps](#)