



5V0-21.20^{Q&As}

VMware Certified Master Specialist (HCI 2020)

Pass VMware 5V0-21.20 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/5v0-21-20.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by VMware
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

An administrator arrives at work and begins their morning checks on a four node, all-flash vSAN Cluster. They notice the vSAN datastore reached 99% capacity due to a single node failure. How can the administrator provide temporary relief?

- A. change FTT=1 with RAID-5 (Erasure coding) to FTT=1 with RAID-1 (Mirroring)
- B. change FTT=1 with RAID-1 (Mirroring) to FTT=1 with RAID-5 (Erasure coding)
- C. change FTT=1 with RAID-1 (Mirroring) to FTT=0 No data redundancy
- D. change FTT=1 with RAID-5 (Erasure coding) to FTT=0 No data redundancy

Correct Answer: B

QUESTION 2

Three months ago, an administrator deployed vRealize Operations Manager from vCenter to manage his newly deployed four-node vSAN 6.7 All-Flash cluster. What must the administrator do to continue using vRealize Operations Dashboards for vSAN?

- A. Reconfigure the vSAN cluster.
- B. Upgrade vRealize Operation Manager.
- C. Apply the correct license to the vSAN cluster.
- D. Reconfigure the vRealize Operations Manager.

Correct Answer: C

QUESTION 3

A failed storage controller has two vSAN disk groups attached. The components contained on the drives in those disk groups are marked Degraded. vSAN reports that some objects do not comply with their assigned storage policy. How is the compliance issue resolved?

- A. Initiate a proactive rebalance to force component repairs.
- B. Degraded components are repaired after CLOM Repair Delay Timer expires.
- C. Rebuilding of the degraded components starts immediately.
- D. Storage policies must be reapplied to all affected objects.

Correct Answer: C

QUESTION 4



What are two factors to consider prior to placing a vSAN node into Maintenance Mode with full data migration? (Choose two.)

- A. vSAN node must be removed from the cluster.
- B. vSAN must be disabled from command line on the host.
- C. Number of fault domains required to satisfy storage policies.
- D. Sufficient vSAN free storage capacity must exist.
- E. VMs registered to the host must be powered off.

Correct Answer: BD

Reference: <https://docs.vmware.com/en/VMware-vSphere/6.7/com.vmware.vsphere.virtualsan.doc/GUID-521EA4BC-E411-47D4-899A-5E0264469866.html>

QUESTION 5

A higher level of resiliency has been requested for an existing vSAN Stretched Cluster. A key requirement will be the addition of a third site to protect against a potential double site failure of the two mirrored sites in the stretched cluster. What solution would meet the resiliency requirement?

- A. Replicate to the third site at the VM level using vSphere Replication.
- B. Configure vSAN Stretched Cluster with FTT=2 to replicate to the third site.
- C. Add the third site to the existing vSAN Stretched Cluster.
- D. Replicate to the third site at the vSAN datastore level using Site Recovery Manager.

Correct Answer: C

[5V0-21.20 PDF Dumps](#)

[5V0-21.20 VCE Dumps](#)

[5V0-21.20 Exam Questions](#)