



600-212^{Q&As}

Implementing Cisco Service Provider Mobility LTE Networks

Pass Cisco 600-212 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/600-212.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

Which network function converts Voice over LTE voice bearer to PSTN voice bearer?

- A. border gateway control function
- B. media gateway function
- C. multimedia resource function
- D. session border controller function

Correct Answer: B

QUESTION 2

Drag the LTE interface on the left to the node on the right that it operates between.

S3	eNodeB and Serving Gateway
S8	Packet Data Network Gateway and Serving Gateway
S5	Packet Data Network Gateway and Serving Gateway (VPLMN)
S1u	Mobility Management Entity and Serving GPRS Support Node

Select and Place:

Drag the LTE interface on the left to the node on the right that it operates between.

S3	eNodeB and Serving Gateway
S8	Packet Data Network Gateway and Serving Gateway
S5	Packet Data Network Gateway and Serving Gateway (VPLMN)
S1u	Mobility Management Entity and Serving GPRS Support Node

Correct Answer:

Drag the LTE interface on the left to the node on the right that it operates between.

	S1u
	S5
	S8
	S3



QUESTION 3

Which two Diameter interfaces are used in Voice over LTE? (Choose two.)

- A. Gn
- B. Gx
- C. ISC
- D. Gi
- E. Cx
- F. Sv

Correct Answer: BE

QUESTION 4

The IP pools that are configured on the Cisco ASR 5000 are used for address allocation. AAA and DHCP have not been enabled from the PGW. Which two parameters does the Cisco ASR 5000 PGW use to generate the subscriber ID for IP address allocation? (Choose two.)

- A. IMEI
- B. MSISDN
- C. EPS bearer ID
- D. IMSI
- E. username

Correct Answer: DE

QUESTION 5

Which option describes the flow of the S6a configuration on the Cisco ASR 5000 system?

- A. MME-service, hss-peer-service, diameter endpoint, peer configuration
- B. MME-service, diameter endpoint, hss-peer-service, peer configuration
- C. MME-service, diameter endpoint, S6a-service, peer configuration
- D. s6a-service, hss-peer-service, diameter endpoint, peer configuration

Correct Answer: A