

6103^{Q&As}

Avaya ERS 8000 and Avaya VSP 9000 Implementation Exam

Pass Avaya 6103 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.passapply.com/6103.html

100% Passing Guarantee 100% Money Back Assurance

Following Questions and Answers are all new published by Avaya Official Exam Center

Instant Download After Purchase

100% Money Back Guarantee

- 😳 365 Days Free Update
- 800,000+ Satisfied Customers





QUESTION 1

What will the boot flag ftpd do to your system on startup?

- A. enable the FTP Server daemon
- B. disable the FTP Server daemon
- C. allow the TFTP transfer of configs D. allow FTP traffic the highest DSCP

Correct Answer: A

QUESTION 2

When configuring a new Ethernet Routing Switch (ERS) 8000 using the default interface, the attempt to load an ACLI configuration fails because the default interface is the CLI.

How is the ACLI interface obtained?

- A. by changing the interface type in the config.cfg file
- B. by changing the ACLI boot flag and saving the boot configuration file
- C. by exiting the CLI and choosing ACLI at the interface manager prompt
- D. by use the abort command, and entering \\'no\\' at the default interface prompt

Correct Answer: C

QUESTION 3

EAPOL and 802.1X are examples of which kind of security within the ERS8000?

- A. Routing
- B. Data Path
- C. Control Path
- D. Management
- Correct Answer: A

QUESTION 4

Which multicast technology, used with the Virtual Services Platform (VSP) 9000, allows the router to determine whether any group members exist on its directly connected networks and switches?

A. IGAP



- B. IGMP
- C. DVMRP
- D. PIM-SM
- Correct Answer: B

QUESTION 5

When troubleshooting an issue with an ERS 8000, running version 7.2, a technician notices that the "Online" LED is steady amber for longer than 3 minutes. This is an indication of a software incompatibility.

What is the first step in resolving this issue?

- A. Use the show chassis command to look for software versions running on the switch.
- B. Use the show compatibility command to verify that all software running is compatible.
- C. Reboot the switch using the boot flags to force the switch to auto-update the software.
- D. Use the show log command to check the system log for indications of communication problems.

Correct Answer: D

6103 PDF Dumps

6103 Study Guide

6103 Exam Questions