

642-732^{Q&As}

Conducting Cisco Unified Wireless Site Survey (CUWSS) v2.0

Pass Cisco 642-732 Exam with 100% Guarantee

Free Download Real Questions & Answers PDF and VCE file from:

https://www.passapply.com/642-732.html

100% Passing Guarantee 100% Money Back Assurance

Following Questions and Answers are all new published by Cisco
Official Exam Center

- Instant Download After Purchase
- 100% Money Back Guarantee
- 365 Days Free Update
- 800,000+ Satisfied Customers



https://www.passapply.com/642-732.html

QUESTION 1

What is the recommended method to protect a wireless outdoor bridge from lightning?

- A. Install the wireless outdoor bridge in a grounded NEMA enclosure.
- B. Install the wireless outdoor bridge inside a building if possible and only have the antenna outside.
- C. Install a fiber-optic link between the wireless outdoor bridge and the antenna.
- D. Install a one-meter segment of fiber-optic cable with a copper-to-fiber-optic transceiver to isolate the wireless outdoor bridge from the network cable plant.
- E. Install a protection frame in the copper portion of the network cable plant to act as a lighting arrestor.

Correct Answer: D

QUESTION 2

Which item is the most common limiting factor in an outdoor coverage for mesh deployment?

- A. 5GHz MAP to RAP backhaul
- B. 2.4GHz MAP to RAP backhaul
- C. 2.4GHz MAP access
- D. 2.4GHz client

Correct Answer: D

QUESTION 3

A network engineer is conducting an active wireless survey. Which four actions must be performed to ensure a successful survey? (Choose four.)

- A. Use the same AP model for the survey that is used in production.
- B. Point the antenna of the survey laptop towards the access point.
- C. Perform the survey when site is empty.
- D. Place the survey laptop antenna on a pole while surveying.
- E. Look for potential barriers of the propagation of RF signals.
- F. Identify areas that have high user density.
- G. Use the same wireless devices that the customer will use.

Correct Answer: AEFG



QUESTION 4

Refer to the exhibit.



Which type of cable connector is displayed that is used to connect antennas to transmitters?

- A. RP-TNC
- B. N
- C. SMA
- D. SMB
- E. MMCX

Correct Answer: B

QUESTION 5

What two factors could cause a post-deployment audit to show a high retransmission rate for the WLAN? (Choose two.)

- A. CRC errors
- B. Rate shifting
- C. CCX compatible clients
- D. High SNR values
- E. High RSSI values

Correct Answer: AB



https://www.passapply.com/642-732.html 2021 Latest passapply 642-732 PDF and VCE dumps Download

Latest 642-732 Dumps

642-732 VCE Dumps

642-732 Exam Questions



To Read the Whole Q&As, please purchase the Complete Version from Our website.

Try our product!

100% Guaranteed Success

100% Money Back Guarantee

365 Days Free Update

Instant Download After Purchase

24x7 Customer Support

Average 99.9% Success Rate

More than 800,000 Satisfied Customers Worldwide

Multi-Platform capabilities - Windows, Mac, Android, iPhone, iPod, iPad, Kindle

We provide exam PDF and VCE of Cisco, Microsoft, IBM, CompTIA, Oracle and other IT Certifications. You can view Vendor list of All Certification Exams offered:

https://www.passapply.com/allproducts

Need Help

Please provide as much detail as possible so we can best assist you. To update a previously submitted ticket:





Any charges made through this site will appear as Global Simulators Limited.

All trademarks are the property of their respective owners.

Copyright © passapply, All Rights Reserved.