70-494^{Q&As}

Re for MCSD: Web Applications

Pass Microsoft 70-494 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.passapply.com/70-494.html

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Microsoft Official Exam Center

⚙ **Instant Download** After Purchase

⚙ **100% Money Back** Guarantee

⚙ **365 Days** Free Update

⚙ **800,000+** Satisfied Customers

QUESTION 1

The service has been deployed to Windows Azure.

Trey Research has provided version 1.3.0.0 of the assembly to support a change in the serialization format. The service must remain available during the transition to the new serialization format.

You need to ensure that the service is using the new assembly.

Which configuration setting should you add to the web.config? (To answer, drag the appropriate configuration elements to the correct location or locations in the answer area. Each configuration element may be used once, more than once, or

not at all. You may need to drag the split bar between panes or scroll to view content.)

Select and Place:


```
codeBase version="1.3.0.0" href="Trey.Serialization.dll"

bindingRedirect oldVersion="1.2.5.0" newVersion="1.3.0.0"

bindingRedirect oldVersion="1.2.0.0" newVersion="1.3.0.0"

runtime

location
```

```
<
>
```

```
<assemblyBinding xmlns="urn:schemas-microsoft-com:asm.v1">
  <dependentAssembly>
    <assemblyIdentity name="Trey.Serialization" />

    <

  </dependentAssembly>
</assemblyBinding>
```

```
</
>
```

Correct Answer:

```
codeBase version="1.3.0.0" href="Trey.Serialization.dll"

bindingRedirect oldVersion="1.2.5.0" newVersion="1.3.0.0"

bindingRedirect oldVersion="1.2.0.0" newVersion="1.3.0.0"

runtime

location
```

```
<  runtime                                                                        >


   <assemblyBinding xmlns="urn:schemas-microsoft-com:asm.v1">
      <dependentAssembly>
         <assemblyIdentity name="Trey.Serialization" />

      <  codeBase version="1.3.0.0" href="Trey.Serialization.dll"

      </dependentAssembly>
   </assemblyBinding>

</  runtime                                                                       >
```

QUESTION 2

You are designing a localized ASP.NET MVC online shopping application that will be deployed to customers in the United States, China, France, and Brazil. The application must support multiple cultures so that content in the appropriate

language is available in each area.

You need to ensure that the content can be viewed in several languages.

How should you implement this feature?

A. Use a resource (.resx) file to provide translations.

B. Use Systems.Collections.Generics.Dictionary to store alternative translations.

C. Ensure that all strings are marked internal to avoid conflict with internal literals.

D. Include language-specific content in the assembly manifest and use .NET culture libraries.

Correct Answer: A

Explanation: A resource file is an XML file that contains the strings that you want to translate into different languages or paths to images. The resource file contains key/value pairs. Each pair is an individual resource. Key names are not case sensitive. For example, a resource file might contain a resource with the key Button1 and the value Submit. You create a separate resource file for each language (for example, English and French) or for a language and culture (for example English [U.K.], English [U.S.]). Each localized resource file has the same key/value pairs; the only difference is that a localized resource file can contain fewer resources than the default resource file. The built-in language fallback process then handles loading the neutral or default resource.

Reference: SP.NET Web Page Resources Overview

QUESTION 3

You need to ensure that only valid parameters are passed to the EditLog action.

How should you build the route? (To answer, select the appropriate options in the answer area.)

Hot Area:

Work Area

```
routes.MapRoute(
    name: "EditLog",
```

[dropdown ▼]

```
id = @"\d+"
url: "RunLog/EditLog/{id}",
action = "EditLog",
defaults: new
constraints: new
```

[dropdown ▼]

```
id = @"\d+"
url: "RunLog/EditLog/{id}",
action = "EditLog",
defaults: new
constraints: new
```

```
    {
        controller = "RunLog",
```

[dropdown ▼]

```
id = @"\d+"
url: "RunLog/EditLog/{id}",
action = "EditLog",
defaults: new
constraints: new
```

```
    },
```

[dropdown ▼]

```
id = @"\d+"
url: "RunLog/EditLog/{id}",
action = "EditLog",
defaults: new
constraints: new
```

```
    {
```

[dropdown ▼]

```
id = @"\d+"
url: "RunLog/EditLog/{id}",
action = "EditLog",
defaults: new
constraints: new
```

```
    }
);
```

Correct Answer:

Work Area

```
routes.MapRoute(
    name: "EditLog",
```

[dropdown ▼]

```
id = @"\d+"
url: "RunLog/EditLog/{id}",
action = "EditLog",
defaults: new
constraints: new
```

[dropdown ▼]

```
id = @"\d+"
url: "RunLog/EditLog/{id}",
action = "EditLog",
defaults: new
constraints: new
```

```
    {
        controller = "RunLog",
```

[dropdown ▼]

```
id = @"\d+"
url: "RunLog/EditLog/{id}",
action = "EditLog",
defaults: new
constraints: new
```

```
    },
```

[dropdown ▼]

```
id = @"\d+"
url: "RunLog/EditLog/{id}",
action = "EditLog",
defaults: new
constraints: new
```

```
    {
```

[dropdown ▼]

```
id = @"\d+"
url: "RunLog/EditLog/{id}",
action = "EditLog",
defaults: new
constraints: new
```

```
    }
    }
);
```

QUESTION 4

You are developing an ASP.NET MVC application. The application has a page that searches for and displays an image stored in a database. Members of the EntityClient namespace are used to access an ADO.NET Entity Framework data model. Images and associated metadata are stored in a database table.

You need to run a query that returns only the image while minimizing the amount of data that is transmitted.

Which method of the EntityCommand type should you use?

A. ExecuteScalar

B. ExecuteDbDataReader

C. ExecuteReader

D. ExecuteNonQuery

Correct Answer: A

Explanation: ExecuteScalar

Executes the command, and returns the first column of the first row in the result set.

Additional columns or rows are ignored.

QUESTION 5

You are developing a .NET application that uses the HttpClient type to call an ASP.NET Web API application. The API call returns a list of customers in JSON format and logs the results.

The URI for the API call is in a variable named address.

You need to make the API call without blocking.

Which code segment should you use?

A. Option A

B. Option B

C. Option C

D. Option D

Correct Answer: A

Explanation: Example: // Create an HttpClient instance

11: HttpClient client = new HttpClient();

12:

13: // Send a request asynchronously continue when complete

14: client.GetAsync(_address).ContinueWith(

15: (requestTask) =>

16: {

17: // Get HTTP response from completed task.

18: HttpResponseMessage response = requestTask.Result;

19:

20: // Check that response was successful or throw exception

21: response.EnsureSuccessStatusCode();

22:

23: // Read response asynchronously as JsonValue and write out top facts for each country

24: response.Content.ReadAsAsync().ContinueWith(

25: (readTask) =>

To Read the Whole Q&As, please purchase the Complete Version from Our website.

Try our product !

100% Guaranteed Success
100% Money Back Guarantee
365 Days Free Update
Instant Download After Purchase
24x7 Customer Support
Average 99.9% Success Rate
More than 800,000 Satisfied Customers Worldwide
Multi-Platform capabilities - Windows, Mac, Android, iPhone, iPod, iPad, Kindle

We provide exam PDF and VCE of Cisco, Microsoft, IBM, CompTIA, Oracle and other IT Certifications.
You can view Vendor list of All Certification Exams offered:

https://www.passapply.com/allproducts

Need Help

Please provide as much detail as possible so we can best assist you.
To update a previously submitted ticket: