



701-100^{Q&As}

DevOps Tools Engineer Exam

Pass Lpi 701-100 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/701-100.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Lpi Official Exam Center

- ⚙ **Instant Download** After Purchase
- ⚙ **100% Money Back** Guarantee
- ⚙ **365 Days** Free Update
- ⚙ **800,000+** Satisfied Customers





QUESTION 1

What is the difference between the commands `git diff` and `git diff --cached`? (Choose TWO correct answers)

- A. `git diff --cached` shows changes of all commits that were not pushed to origin yet
- B. `git diff` shows changes that were not added to the next commit
- C. `git diff` and `git diff --cached` always lead to the same result if a repository does not have at least one remote repository
- D. `git diff --cached` shows changes that will be included in the next commit
- E. `git diff --cached` shows changes included in the last successful commit of the current branch

Correct Answer: BD

QUESTION 2

Which of the following mechanisms are used for service discovery in a container environment? (Choose two correct answers.)

- A. The container platform offers a command like `docker service discover` which should be run within a container.
- B. The container platform sets environment variables containing service information within the containers.
- C. The container platform lists localhost ports assigned to containers in each container's `/etc/services` file.
- D. The container platform mounts the sockets for all available services into the container's file systems.
- E. The container platform maintains DNS records which point to containers offering a specific service.

Correct Answer: BE

QUESTION 3

Which of the following commands lists the nodes in a Docker Swarm cluster?

- A. `docker-swarm listnodes`
- B. `docker engine ls`
- C. `docker node ls`
- D. `docker machine ls`
- E. `docker swarm nodes`

Correct Answer: C

<https://docs.docker.com/engine/swarm/manage-nodes/>



QUESTION 4

The file myapp.yml exists with the following content:

version: "3" services: frontend: image: frontend ports:

"80:80" backend: image: backend deploy: replicas: 2

Given that file was successfully processed by docker stack deploy myapp -compose--file myapp.yml, which of the following objects might be created? (Choose THREE correct answers)

- A. An overlay network called myapp_default.
- B. A node called myapp_frontend.
- C. A container called myapp_backend.2.ymia7v7of5g02j3ji1btt8z.
- D. A volumen called myapp_frontend.1.
- E. A service called myapp_frontend.

Correct Answer: ABD

QUESTION 5

What is the default URL Prometheus tries to retrieve from a target when gathering monitoring information? (Specify the Full URL, without any host name or scheme)

A. The default URL that Prometheus tries to retrieve when gathering monitoring information depends on the specific target and the configuration of Prometheus at that time. Prometheus's default behavior is to try to retrieve a scrape target's metrics data from a pre-defined location. For example, if you are monitoring a target that exposes its metrics data on port 8080 of the local network interface, the default URL retrieved by Prometheus would be http://localhost:8080/metrics. However, if the target's metrics data is not on the local interface but rather on another IP address or domain, the URL would change accordingly. Prometheus's default behavior can be modified through configuration files or command-line flags. Therefore, the specific default URL depends on the specific configuration of Prometheus.

Correct Answer: A

[Latest 701-100 Dumps](#)

[701-100 PDF Dumps](#)

[701-100 Braindumps](#)