



9L0-012^{Q&As}

Mac Service Certification Exam

Pass Apple 9L0-012 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/9L0-012.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Apple
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers






QUESTION 1

To power on the system, which of the following can be used on the MacBook Pro (Retina, Mid 2012) and MacBook Pro (Retina, 15-inch, Early 2013 and Late 2013) logic boards?

- A. Two switches that can be flipped
- B. Two ports that be activated
- C. Two pads that can be shorted
- D. Two buttons that can be pressed

Correct Answer: D

QUESTION 2



Examine the image. You have a cable with a connector of this shape. What type of cable might this be? SELECT TWO.

- A. Thunderbolt
- B. Mini DisplayPort
- C. USB 2.0
- D. FireWire800
- E. Mini DVI

Correct Answer: AB



Reference: <http://arstechnica.com/apple/2011/02/thunderbolt-smokes-usb-firewire-with-10gbpsthroughput/>

QUESTION 3

Which of the following software tools can detect malfunctioning thermal sensors on MacBook Air (Mid 2013) models?
SELECT TWO

- A. System Information
- B. Apple Service Toolkit (AST)
- C. Apple Service Diagnostics (ASD)
- D. Thermal Sensor Diagnostics (TD)
- E. Thermal Service Diagnostics (TSD)

Correct Answer: BC

Reference: <http://mdex-nn.ru/uploads/newmbp15.pdf> (page 6, software tools)

QUESTION 4

You are about to replace a MacBook Air (11-inch, Mid 2013) logic board. Which of the following is the most important step you should take immediately after removing the bottom case?

- A. Remove the thermal module.
- B. Install the battery cover.
- C. Remove the SSD carrier
- D. Remove the battery.

Correct Answer: D

QUESTION 5

What caution should a technician be aware of before attempting to remove hard drives or optical drive carrier from a MacPro (Mid 2012)?

- A. The rear latch must be lifted or the drives are locked in a place.
- B. The rear latch should be in the closed position to unlock drives.
- C. The hard drives must be unscrewed from the carrier before removal.



D. The optical drive screws must be removed before sliding the carrier out of enclosure.

Correct Answer: D

[9L0-012 PDF Dumps](#)

[9L0-012 Study Guide](#)

[9L0-012 Braindumps](#)