C4090-454$^{Q\&As}$

IBM High-End Tape Technical Solutions V7

Pass IBM C4090-454 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.passapply.com/c4090-454.html

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by IBM Official Exam Center

QUESTION 1

What drive types are supported in the IBM TS3300 Tape Library?

A. LTO drives only

B. TS11x0 drives only

C. Both LTO and DLT drives

D. Both LTO and TS11x0 drives

Correct Answer: B

QUESTION 2

Which of the following best describes the TS1140 EastSync function?

A. Matches the input and output data rates of the main buffer

B. Uses a non-volatile cache for small transaction sizes (less than 204 MB compressed)

C. Reads forward to the requested target block rather than performing a higher-speed tape motion

D. Improves synchronized write performance for larger transactions (greater than 204 MB compressed)

Correct Answer: B

QUESTION 3

In a TS3500 with ALMS enabled, which task can be completed by using the Tape Library Specialist Web interlace only, and not by using the operator panel?

A. Creating or removing a logical library

B. View or change the preferred zone of an accessory

C. Disabling or changing the speed of the Ethernet link

D. Installing licensed features of the library such as capacity on demand

Correct Answer: A

QUESTION 4

A customer has installed two TS7700 Virtualization Engines in a grid configuration for disaster recovery. Cluster U is local to the production hosts, and Cluster 1 is located in the remote DR center with no host processors. They want to

maximize the probability that recently written logical volumes are in the cache of Cluster 1 in case of a loss of Cluster U, while maintaining copies in both clusters. Which Copy Consistency Point settings are most appropriate to use?

A. Cluster U = RD. Cluster 1 = RD

B. Cluster U = RD. Cluster 1 = NR

C. Cluster U = DR. Cluster 1 = DR

D. Cluster U = NR, Cluster 1 = RN

Correct Answer: C

QUESTION 5

What is the maximum number of 3490 control units that can be defined in HOD for a TS7700?

A. 16

B. 32

C. 64

D. 256

Correct Answer: A

C4090-454 Study Guide   C4090-454 Exam Questions   C4090-454 Braindumps