



CCB-400^{Q&As}

Cloudera Certified Specialist in Apache HBase

Pass Cloudera CCB-400 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/ccb-400.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Cloudera
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

Your client is writing to a region when the RegionServer crashes. At what point in the write is your data secure?

- A. From the moment the RegionServer wrote to the WAL (write-ahead log)
- B. From the moment the RegionServer returned the call
- C. From the moment the RegionServer received the call
- D. From the moment the RegionServer wrote to the MemStore

Correct Answer: A

QUESTION 2

You have a "Users" table in HBase and you would like to insert a row that consists of a UserID, "jsmith70" and an email address, "jane@example.com". The table has a single Column Family named "Meta" and the row key will be the user's ID. The shell command you should use to complete this is:

- A. `put `Users`, `jsmith70`, `jane@example.com``
- B. `put `Users`, `UserID:jsmith70`, `Email:jane@example.com``
- C. `put `Users`, `jsmith70`, `Meta:Email`, `jane@example.com``
- D. `put `Users`, `Meta:UserID`, `jsmith70`, `Meta:Email`, `jane@example.com``

Correct Answer: B

QUESTION 3

You need to insert a cell with a specific timestamp (version) 13353903160532. Which of the following is true?

- A. The timestamp for the entire row must be updated to 13353903160532
- B. The Put class allows setting a cell specific timestamp
- C. The Put class allows setting a column family-specific timestamp
- D. The HTable class allows you to temporarily roll back the newer versions of the cell

Correct Answer: B

QUESTION 4

You need to create a "WebLogs" table in HBase. The table will consist of a single Column Family called "Errors" and two column qualifiers, "IP" and "URL". The shell command you should use to create the table is:



- A. create\\WebLogs\,{NAME =>\\Errors:IP\, NAME =>\\Errors:URL\}
- B. create\\WebLogs\,\\Errors\,{NAME =>\\IP\, NAME =>\\URL\}
- C. create\\WebLogs\,\\Errors:IP\,\\Errors:URL\
- D. create\\WebLogs\,\\Errors\

Correct Answer: C

QUESTION 5

Your client connects to HBase for the first time to read a row user_1234 located in a table Users. What process does your client use to find the correct RegionServer to which it should send the request?

- A. The client looks up the location of ROOT, in which it looks up the location of META, in which it looks up the location of the correct Users region.
- B. The client looks up the location of the master, in which it looks up the location of META, in which it looks up the location of the correct Users region.
- C. The client looks up the location of ROOT in which it looks up the location of the correct Users region.
- D. The client queries the master to find the location of the Users table.

Correct Answer: B

[Latest CCB-400 Dumps](#)

[CCB-400 Practice Test](#)

[CCB-400 Study Guide](#)